

---

# **AWS WAF**

## **Developer Guide**

### **API Version 2015-08-24**



## **AWS WAF: Developer Guide**

Copyright © 2016 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

## Table of Contents

What is AWS WAF? .....	1
How AWS WAF Works .....	2
AWS WAF Pricing .....	3
PCI DSS Compliance .....	3
AWS Identity and Access Management .....	3
Setting Up for AWS WAF .....	5
Step 1: Sign Up for an AWS Account .....	5
Step 2: Create an IAM User .....	5
Step 3: Download Tools .....	7
Getting Started with AWS WAF .....	8
Step 1: Set Up for AWS WAF .....	9
Step 2: Start the Wizard .....	9
Step 3: Create an IP Match Condition .....	9
Step 4: Create a String Match Condition .....	10
Step 5: Create a SQL Injection Match Condition .....	11
Step 6: (Optional) Create Additional Conditions .....	12
Step 7: Create a Rule and Add Conditions .....	12
Step 8: Add the Rule to a Web ACL .....	13
Step 9: Associate a Web ACL with a CloudFront Distribution .....	14
Step 10: Clean Up Your Resources .....	14
Tutorials .....	17
Tutorial: Quickly Setting Up AWS WAF Protection Against Common Attacks .....	17
Solution Overview .....	18
Step 1: Create an AWS CloudFormation Stack that Sets Up AWS WAF Protection Against Common Attacks .....	20
Step 2: Associate a Web ACL with a CloudFront Distribution .....	33
Step 3: (Optional) Add IP Addresses to the IP Match Condition .....	22
Step 4: (Optional) Update the Web ACL to Block Large Bodies .....	22
Step 5: (Optional) Delete Your AWS CloudFormation Stack .....	23
Related Resources .....	36
Tutorial: Blocking IP Addresses that Exceed Request Limits .....	23
Solution Overview .....	24
Step 1: Create an AWS CloudFormation Stack for Rate-Based Blocking .....	25
Step 2: Associate a Web ACL with a CloudFront Distribution .....	26
Step 3: (Optional) Edit AWS CloudFormation Parameter Values .....	28
Step 4: (Optional) Test Your Thresholds and IP Rules .....	28
Step 5: (Optional) Delete Your AWS CloudFormation Stack .....	29
Related Resources .....	36
Tutorial: Blocking IP Addresses that Submit Bad Requests .....	29
Solution Overview .....	30
Step 1: Create an AWS CloudFormation Stack for Blocking IP Addresses that Submit Bad Requests .....	31
Step 2: Associate a Web ACL and a CloudFront Distribution .....	33
Step 2: Associate a Web ACL with a CloudFront Distribution .....	33
Step 3: (Optional) Edit AWS CloudFormation Parameter Values .....	34
Step 4: (Optional) Test Your Thresholds and IP Rules .....	35
Step 5: (Optional) Delete Your AWS CloudFormation Stack .....	35
Related Resources .....	36
Creating and Configuring a Web Access Control List (Web ACL) .....	37
Deciding on the Default Action for a Web ACL .....	38
Working with Cross-site Scripting Match Conditions .....	38
Creating Cross-site Scripting Match Conditions .....	39
Values that You Specify When You Create or Edit Cross-site Scripting Match Conditions .....	39
Adding and Deleting Filters in a Cross-site Scripting Match Condition .....	41
Deleting Cross-site Scripting Match Conditions .....	41

Working with IP Match Conditions .....	42
Creating an IP Match Condition .....	42
Editing IP Match Conditions .....	43
Deleting IP Match Conditions .....	44
Working with Size Constraint Conditions .....	44
Creating Size Constraint Conditions .....	45
Values that You Specify When You Create or Edit Size Constraint Conditions .....	45
Adding and Deleting Filters in a Size Constraint Condition .....	47
Deleting Size Constraint Conditions .....	48
Working with SQL Injection Match Conditions .....	48
Creating SQL Injection Match Conditions .....	48
Values that You Specify When You Create or Edit SQL Injection Match Conditions .....	49
Adding and Deleting Filters in a SQL Injection Match Condition .....	51
Deleting SQL Injection Match Conditions .....	51
Working with String Match Conditions .....	52
Creating a String Match Condition .....	52
Values that You Specify When You Create or Edit String Match Conditions .....	53
Adding and Deleting Filters in a String Match Condition .....	55
Deleting String Match Conditions .....	55
Working with Rules .....	56
Creating a Rule and Adding Conditions .....	56
Adding and Removing Conditions in a Rule .....	57
Deleting a Rule .....	58
Listing the Web ACLs that Include a Specified Rule .....	59
Working with Web ACLs .....	59
Creating a Web ACL .....	59
Associating or Disassociating a Web ACL with a CloudFront Distribution .....	62
Editing a Web ACL .....	62
Deleting a Web ACL .....	63
Testing Web ACLs .....	64
Counting the Web Requests that Match the Rules in a Web ACL .....	64
Viewing a Sample of the Web Requests that CloudFront has Forwarded to AWS WAF .....	65
Logging AWS WAF API Calls with AWS CloudTrail .....	67
AWS WAF Information in CloudTrail .....	67
Understanding AWS WAF Log File Entries .....	68
How AWS WAF Works with Amazon CloudFront Features .....	71
Using AWS WAF with CloudFront Custom Error Pages .....	71
Using AWS WAF with CloudFront Geo Restriction .....	72
Choosing the HTTP Methods that CloudFront Responds to .....	72
Authentication and Access Control .....	73
Authentication .....	73
Access Control .....	74
Overview of Managing Access .....	75
Topics .....	75
AWS WAF Resources and Operations .....	75
Understanding Resource Ownership .....	76
Managing Access to Resources .....	76
Specifying Policy Elements: Actions, Effects, Resources, and Principals .....	78
Specifying Conditions in a Policy .....	78
Using Identity-Based Policies (IAM Policies) .....	79
Topics .....	80
Permissions Required to Use the AWS WAF Console .....	80
AWS Managed (Predefined) Policies for AWS WAF .....	80
Customer Managed Policy Examples .....	80
AWS WAF API Permissions Reference .....	83
Using the AWS WAF API .....	87
Using the AWS SDKs .....	87
Making HTTPS Requests to AWS WAF .....	87

Request URI .....	87
HTTP Headers .....	87
HTTP Request Body .....	89
HTTP Responses .....	89
Error Responses .....	90
Authenticating Requests .....	90
Limits .....	92
Resources .....	93
AWS Resources .....	93
Document History .....	94
AWS Glossary .....	96

# What is AWS WAF?

---

AWS WAF is a web application firewall that lets you monitor the HTTP and HTTPS requests that are forwarded to Amazon CloudFront and lets you control access to your content. Based on conditions that you specify, such as the IP addresses that requests originate from or the values of query strings, CloudFront responds to requests either with the requested content or with an HTTP 403 status code (Forbidden). You can also configure CloudFront to return a custom error page when a request is blocked.

At the simplest level, AWS WAF lets you choose one of the following behaviors:

- **Allow all requests except the ones that you specify** – This is useful when you want CloudFront to serve content for a public website but you also want to block requests from attackers.
- **Block all requests except the ones that you specify** – This is useful when you want CloudFront to serve content for a restricted website whose users are readily identifiable by properties in web requests such as the IP addresses they use to browse to the website.
- **Count the requests that match the properties that you specify** – When you want to allow or block requests based on new properties in web requests, you can first configure AWS WAF to count the requests that match those properties without allowing or blocking those requests. This lets you confirm that you didn't accidentally configure AWS WAF to block all of the traffic to your website. When you're confident that you specified the correct properties, you can change the behavior to allow or block requests.

Using AWS WAF has several potential benefits:

- Additional protection against web attacks using conditions that you specify. You can define conditions by using characteristics of web requests such as the following:
  - The IP addresses that the requests originate from
  - The values in request headers
  - Strings that appear in the requests
  - The length of requests
  - The presence of SQL code that is likely to be malicious (this is known as SQL injection)
  - The presence of a script that is likely to be malicious (this is known as cross-site scripting)
- Rules that you can reuse for multiple web applications
- Real-time metrics and sampled web requests
- Automated administration using the AWS WAF API

## How AWS WAF Works

You control how Amazon CloudFront responds to web requests by creating conditions, rules, and web access control lists (web ACLs).

### Conditions

Conditions define the basic characteristics that you want AWS WAF to watch for in web requests:

- Scripts that are likely to be malicious. Attackers embed scripts that can exploit vulnerabilities in web applications; this is known as cross-site scripting.
- The IP addresses or address ranges that requests originate from.
- The length of specified parts of the request, such as the query string.
- SQL code that is likely to be malicious. Attackers try to extract data from your database by embedding malicious SQL code in a web request; this is known as SQL injection.
- Strings that appear in the request, for example, values that appear in the `User-Agent` header or text strings that appear in the query string.

Some conditions take multiple values. For example, you can specify up to 1000 IP addresses or IP address ranges in an IP condition.

### Rules

You combine conditions into rules to precisely target the requests that you want to allow or block. For example, based on recent requests that you've seen from an attacker, you might create a rule that includes the following conditions:

- The requests come from 192.0.2.44.
- They contain the value `BadBot` in the `User-Agent` header.
- They appear to include malicious SQL code in the query string.

When a rule includes all three of these conditions, AWS WAF looks for requests that match all three conditions—it **ANDS** the conditions together.

### Web ACLs

Finally, you combine rules into a web ACL. This is where you define an action for each rule—allow, block, or count—and a default action:

#### An action for each rule

When a web request matches all of the conditions in a rule, AWS WAF can either allow the request to be forwarded to CloudFront or block the request. You specify the action that you want AWS WAF to perform for each rule.

AWS WAF compares a request with the rules in a web ACL in the order in which you listed the rules and takes the action that is associated with the first rule that the request matches. For example, if a web request matches one rule that allows requests and another rule that blocks requests, AWS WAF will either allow or block the request depending on which rule is listed first.

If you want to test a new rule before you start using it, you can also configure AWS WAF to count the requests that meet all of the conditions in the rule. As with rules that allow or block requests, a rule that counts requests is affected by its position in the list of rules in the web ACL. For example, if a web request matches a rule that allows requests and another rule that counts requests, and if the rule that allows requests is listed first, the request won't be counted.

#### A default action

The default action determines whether AWS WAF allows or blocks a request that does not match all of the conditions in any of the rules in the web ACL. For example, suppose you create a web ACL and add only the rule that you defined before:

- The requests come from 192.0.2.44.
- They contain the value `BadBot` in the `User-Agent` header.
- They appear include malicious SQL code in the query string.

If a request doesn't meet all three conditions in the rule and if the default action is `ALLOW`, AWS WAF forwards the request to CloudFront, and CloudFront responds with the requested object.

If you add two or more rules to a web ACL, AWS WAF performs the default action only if a request does not satisfy all of the conditions in any of the rules. For example, suppose you add a second rule that contains one condition:

- The requests that contain the value `BIGBadBot` in the `User-Agent` header.

AWS WAF performs the default action only when a request does not meet all three conditions in the first rule and does not meet the one condition in the second rule.

On rare occasions, AWS WAF might encounter an internal error that delays the response to CloudFront about whether to allow or block a request. On those occasions, CloudFront either serves the content from the edge location or forwards the request to your origin. For more information, see [How CloudFront Delivers Content](#) in the *Amazon CloudFront Developer Guide*.

## AWS WAF Pricing

As with other AWS products, there are no contracts or minimum commitments for using AWS WAF. You pay only for the web ACLs and rules that you create, and for the number of HTTP requests that AWS WAF inspects. For more information, see [AWS WAF Pricing](#).

## PCI DSS Compliance

AWS WAF is now a Payment Card Industry (PCI) Data Security Standard (DSS) 3.2 compliant service. The PCI Standards Council published PCI DSS version 3.2 in April 2016 as the most updated set of requirements available. PCI DSS 3.2 has revised and clarified the online credit card transaction requirements around encryption, access control, change management, application security, and risk management programs.

For more information about AWS and PCI DSS 3.2 compliance, see [AWS Becomes First Cloud Service Provider to Adopt New PCI DSS 3.2](#) on the AWS Security Blog. For more information about PCI DSS version 3.2, see [PCI DSS 3.2: What's New?](#).

## AWS Identity and Access Management

AWS WAF integrates with AWS Identity and Access Management (IAM), a service that lets your organization do the following:

- Create users and groups under your organization's AWS account
- Easily share your AWS account resources between the users in the account
- Assign unique security credentials to each user
- Granularly control users access to services and resources
- Get a single AWS bill for all users in the AWS account

For example, you can use IAM with AWS WAF to control which users in your AWS account can create a new web ACL.

For information about using AWS WAF with IAM, see [Authentication and Access Control for AWS WAF](#) (p. 73).



For general information about IAM, see the following documentation:

- [AWS Identity and Access Management \(IAM\)](#)
- [IAM Getting Started Guide](#)
- [IAM User Guide](#)

# Setting Up for AWS WAF

---

Before you use AWS WAF for the first time, complete the following tasks:

- [Step 1: Sign Up for an AWS Account \(p. 5\)](#)
- [Step 2: Create an IAM User \(p. 5\)](#)
- [Step 3: Download Tools \(p. 7\)](#)

## Step 1: Sign Up for an AWS Account

When you sign up for Amazon Web Services (AWS), your AWS account is automatically signed up for all services in AWS, including AWS WAF. You are charged only for the services that you use.

If you have an AWS account already, skip to the next task. If you don't have an AWS account, use the following procedure to create one.

### To sign up for AWS

1. Open <http://aws.amazon.com/> and click **Sign Up**.
2. Follow the on-screen instructions.

Part of the sign-up procedure involves receiving a phone call and entering a PIN using the phone keypad.

Note your AWS account number, because you'll need it for the next task.

## Step 2: Create an IAM User

To use the AWS WAF console, you need to sign in to confirm that you have permission to perform AWS WAF operations. You can use the credentials for your AWS account, but we don't recommend it. For greater security and control of your account, we recommend that you use AWS Identity and Access Management (IAM) to do the following:

- Create an IAM user account for yourself or your business
- Either add the IAM user account to an IAM group that has administrative permissions, or grant the IAM user account administrative permissions directly

You can then sign in to the AWS WAF console (and other service consoles) by using a special URL and the credentials for the IAM user. You can also add other users to the IAM user account, and control their level of access to AWS services and to your resources.

**Note**

For information about creating access keys to access AWS WAF by using the [AWS Command Line Interface](#) (AWS CLI), [Tools for Windows PowerShell](#), the [AWS SDKs](#), or the AWS WAF API, see [Managing Access Keys for IAM Users](#).

If you signed up for AWS but have not created an IAM user for yourself, you can create one using the IAM console. If you aren't familiar with using the console, see [Working with the AWS Management Console](#) for an overview.

**To create a group for administrators**

1. Sign in to the Identity and Access Management (IAM) console at <https://console.aws.amazon.com/iam/>.
2. In the navigation pane, choose **Groups**, and then choose **Create New Group**.
3. For **Group Name**, type a name for your group, such as **Administrators**, and then choose **Next Step**.
4. In the list of policies, select the check box next to the **AdministratorAccess** policy. You can use the **Filter** menu and the **Search** box to filter the list of policies.
5. Choose **Next Step**, and then choose **Create Group**.

Your new group is listed under **Group Name**.

**To create an IAM user for yourself, add the user to the administrators group, and create a password for the user**

1. In the navigation pane, choose **Users**, and then choose **Create New Users**.
2. In box **1**, type a user name.
3. Clear the check box next to **Generate an access key for each user**.
4. Choose **Create**.
5. In the list of users, choose the name (not the check box) of the user you just created. You can use the **Search** box to search for the user name.
6. Choose the **Groups** tab and then choose **Add User to Groups**.
7. Select the check box next to the administrators group. Then choose **Add to Groups**.
8. Choose the **Security Credentials** tab. Under **Sign-In Credentials**, choose **Manage Password**.
9. Select **Assign a custom password**. Then type a password in the **Password** and **Confirm Password** boxes. When you are finished, choose **Apply**.

To sign in as this new IAM user, sign out of the AWS console, then use the following URL, where *your\_aws\_account\_id* is your AWS account number without the hyphens (for example, if your AWS account number is 1234-5678-9012, your AWS account ID is 123456789012):

```
https://your_aws_account_id.signin.aws.amazon.com/console/
```

Enter the IAM user name and password that you just created. When you're signed in, the navigation bar displays "*your\_user\_name @ your\_aws\_account\_id*".

If you don't want the URL for your sign-in page to contain your AWS account ID, you can create an account alias. From the IAM dashboard, click **Customize** and enter an alias, such as your company name. To sign in after you create an account alias, use the following URL:

```
https://your_account_alias.signin.aws.amazon.com/console/
```

To verify the sign-in link for IAM users for your account, open the IAM console and check under the **IAM users sign-in link** on the dashboard.

## Step 3: Download Tools

The AWS Management Console includes a console for AWS WAF, but if you want to access AWS WAF programmatically, the following documentation and tools will help you:

- If you want to call the AWS WAF API without having to handle low-level details like assembling raw HTTP requests, you can use an AWS SDK. The AWS SDKs provide functions and data types that encapsulate the functionality of AWS WAF and other AWS services. To download an AWS SDK, see the applicable page, which also includes prerequisites and installation instructions:

- [Java](#)
- [JavaScript](#)
- [.NET](#)
- [Node.js](#)
- [PHP](#)
- [Python](#)
- [Ruby](#)

For a complete list of AWS SDKs, see [Tools for Amazon Web Services](#).

- If you're using a programming language for which AWS doesn't provide an SDK, the [AWS WAF API Reference](#) documents the operations that AWS WAF supports.
- The AWS Command Line Interface (AWS CLI) supports AWS WAF. The AWS CLI lets you control multiple AWS services from the command line and automate them through scripts. For more information, see [AWS Command Line Interface](#).
- AWS Tools for Windows PowerShell supports AWS WAF. For more information, see [AWS Tools for Windows PowerShell Reference](#).

# Getting Started with AWS WAF

---

The example in this topic gives you a quick overview of how to use the AWS WAF to perform the following tasks:

- Get set up to use AWS WAF
- Start the **Set up a web access control list** wizard on the AWS WAF console, and specify the conditions that you want to use to filter web requests such as the IP addresses that the requests originate from and values in the request that are used only by attackers.
- Add the conditions to a rule. Rules let you target exactly the web requests that you want to block or allow; a web request must match all of the conditions in a rule before AWS WAF will block or allow requests based on the conditions that you specify.
- Add the rules to a web access control list (web ACL). This is where you specify whether you want to block web requests or allow them based on the conditions that you added to each rule.
- Specify a default action, block or allow. This is the action that AWS WAF takes when a web request doesn't match any of your rules.
- Choose the Amazon CloudFront distribution for which you want AWS WAF to inspect web requests.

## Note

AWS typically will bill you less than US\$0.25 per day for the resources that you create during this tutorial. When you're finished, we recommend that you delete the resources to prevent incurring unnecessary charges.

## Topics

- [Step 1: Set Up for AWS WAF \(p. 9\)](#)
- [Step 2: Start the Wizard \(p. 9\)](#)
- [Step 3: Create an IP Match Condition \(p. 9\)](#)
- [Step 4: Create a String Match Condition \(p. 10\)](#)
- [Step 5: Create a SQL Injection Match Condition \(p. 11\)](#)
- [Step 6: \(Optional\) Create Additional Conditions \(p. 12\)](#)
- [Step 7: Create a Rule and Add Conditions \(p. 12\)](#)
- [Step 8: Add the Rule to a Web ACL \(p. 13\)](#)
- [Step 9: Associate a Web ACL with a CloudFront Distribution \(p. 14\)](#)
- [Step 10: Clean Up Your Resources \(p. 14\)](#)

## Step 1: Set Up for AWS WAF

If you already signed up for an AWS account and created an IAM user as described in [Setting Up for AWS WAF \(p. 5\)](#), go to [Step 2: Start the Wizard \(p. 9\)](#).

If not, go to [Setting Up for AWS WAF \(p. 5\)](#) and perform at least the first two steps. (You can skip downloading tools for now because this Getting Started topic focuses on using the AWS WAF console.)

## Step 2: Start the Wizard

The **Set up a web access control list (Web ACL)** wizard guides you through the process of configuring AWS WAF to block or allow web requests based on conditions that you specify, such as the IP addresses that the requests originate from or values in the requests.

### To start the wizard

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. On the AWS WAF **Getting started** page, click **Get started**.
3. (Optional) Review the **Concepts overview** page.
4. Choose **Next**.
5. On the **Create web ACL** page, type a value in the **Web ACL name** field. The name that you specify also appears in the CloudFront console in the settings for the distribution that you associate with this web ACL.

#### Note

You can't change the name after you create the web ACL.

6. Type a value in the **CloudWatch metric name** field. The name can contain only alphanumeric characters (A-Z, a-z, 0-9); it can't contain whitespace.

#### Note

You can't change the name after you create the web ACL.

7. Choose **Next**.

## Step 3: Create an IP Match Condition

An IP match condition specifies the IP addresses or IP address ranges that requests originate from. Later in the wizard, you specify whether you want to allow requests or block requests that originate from the specified addresses.

#### Note

For more information about IP match conditions, see [Working with IP Match Conditions \(p. 42\)](#).

### To create an IP match condition

1. On the **Create conditions** page of the wizard, choose **Create IP match condition**.
2. In the **Name** field, type a name. The name can contain only alphanumeric characters.
3. In the **IP address or range** field, type **192.0.2.0/24**. This IP address range, specified in CIDR notation, includes the IP addresses from 192.0.2.0 to 192.0.2.255. (The 192.0.2.0/24 IP address range is reserved for examples, so no web requests will originate from these IP addresses.)

You can specify /8, /16, /24, and /32 IP address ranges. (To specify a single IP address, such as 192.0.2.44, type **192.0.2.44/32**.) Other ranges aren't supported.

For more information about CIDR notation, see the Wikipedia article [Classless Inter-Domain Routing](#).

4. Choose **Create**.

## Step 4: Create a String Match Condition

A string match condition identifies the strings that you want AWS WAF to search for in a request, such as a specified value in a header or in a query string. Usually, a string will consist of printable ASCII characters, but you can specify any character from hexadecimal 0x00 to 0xFF (decimal 0 to 255). Later in the wizard, you specify whether you want to allow or block requests that contain the specified strings.

### Note

For more information about string match conditions, see [Working with String Match Conditions](#) (p. 52).

### To create a string match condition

1. On the **Create conditions** page of the wizard, choose **Create string match condition**.
2. Enter the following values:

#### Name

Type a name. The name can contain only alphanumeric characters.

#### Part of the request to filter on

Choose the part of the web request that you want AWS WAF to inspect for a specified string.

For this example, choose **Header**.

#### Note

If you choose **Body** for the value of **Part of the request to filter on**, AWS WAF inspects only the first 8192 bytes (8 KB) because CloudFront forwards only the first 8192 bytes for inspection. To allow or block requests for which the body is longer than 8192 bytes, you can create a size constraint condition. (AWS WAF gets the length of the body from the request headers.) For more information, see [Working with Size Constraint Conditions](#) (p. 44).

#### Header (Required if "Part of the request to filter on" is "Header")

Because you chose **Header** for **Part of the request to filter on**, you need to specify which header you want AWS WAF to inspect. Type **User-Agent**. (This value is not case sensitive.)

#### Match type

Choose where the specified string must appear in the **User-Agent** header, for example, at the beginning, at the end, or anywhere in the string.

For this example, choose **Exactly matches**, which indicates that AWS WAF inspects web requests for a header value that is identical to the value that you specify.

#### Transformation

In an effort to bypass AWS WAF, attackers use unusual formatting in web requests, for example, by adding whitespace or by URL-encoding some or all of the request. Transformations convert the web request to a more standard format by removing whitespace, URL-decoding the request, or performing other operations that eliminate much of the unusual formatting that attackers commonly use.

For this example, choose **None**.

#### Value is base64 encoded

When the value that you type in **Value to match** is already base64-encoded, select this check box.

For this example, don't select the check box.

**Value to match**

Specify the value that you want AWS WAF to search for in the part of web requests that you indicated in **Part of the request to filter on**. Use the format that you specified in **String format**.

For this example, type **BadBot**. AWS WAF will inspect the `User-Agent` header in web requests for the value **BadBot**.

The maximum length of **Value to match** is 50 bytes. If you want to specify a base64-encoded value, the limit is 50 bytes before encoding.

3. If you want AWS WAF to inspect web requests for multiple values, such as a `User-Agent` header that contains `BadBot` and a query string that contains `BadParameter`, you have two choices:
  - If you want to allow or block web requests only when they contain both values (**AND**), you create one string match condition for each value.
  - If you want to allow or block web requests when they contain either value or both (**OR**), you add both values to the same string match condition.

For this example, choose **Create**.

## Step 5: Create a SQL Injection Match Condition

A SQL injection match condition identifies the part of web requests, such as a header or a query string, that you want AWS WAF to inspect for malicious SQL code. Attackers use SQL queries to extract data from your database. Later in the wizard, you specify whether you want to allow requests or block requests that appear to contain malicious SQL code.

**Note**

For more information about string match conditions, see [Working with SQL Injection Match Conditions \(p. 48\)](#).

### To create a SQL injection match condition

1. On the **Create conditions** page of the wizard, choose **Create SQL injection condition**.
2. Enter the following values:

**SQL injection match set name**

Type a name.

**Part of the request to filter on**

Choose the part of web requests that you want AWS WAF to inspect for malicious SQL code.

For this example, choose **Query string**.

**Note**

If you choose **Body** for the value of **Part of the request to filter on**, AWS WAF inspects only the first 8192 bytes (8 KB) because CloudFront forwards only the first 8192 bytes for inspection. To allow or block requests for which the body is longer than 8192 bytes, you can create a size constraint condition. (AWS WAF gets the length of the body from the request headers.) For more information, see [Working with Size Constraint Conditions \(p. 44\)](#).

**Transformation**

For this example, choose **URL decode**.



Attackers use unusual formatting, such as URL encoding, in an effort to bypass AWS WAF. The **URL decode** option eliminates some of that formatting in the web request before AWS WAF inspects the request.

3. Choose **Create**.
4. Choose **Next**.

## Step 6: (Optional) Create Additional Conditions

AWS WAF includes other conditions, including the following:

- **Size constraint conditions** – Identifies the part of web requests, such as a header or a query string, that you want AWS WAF to check for length. For more information, see [Working with Size Constraint Conditions \(p. 44\)](#).
- **Cross-site scripting match conditions** – Identifies the part of web requests, such as a header or a query string, that you want AWS WAF to inspect for malicious scripts. For more information, see [Working with Cross-site Scripting Match Conditions \(p. 38\)](#).

You can optionally create these conditions now, or you can skip to [Step 7: Create a Rule and Add Conditions \(p. 12\)](#).

## Step 7: Create a Rule and Add Conditions

You create a rule to specify the conditions that you want AWS WAF to search for in web requests. If you add more than one condition to a rule, a web request must match all of the conditions in the rule for AWS WAF to allow or block requests based on that rule.

### Note

For more information about rules, see [Working with Rules \(p. 56\)](#).

### To create a rule and add conditions

1. On the **Create rules** page of the wizard, choose **Create rule**.
2. Type the following values:

#### Name

Type a name. The name can contain only alphanumeric characters.

#### CloudWatch metric name

Type a name for the CloudWatch metric that AWS WAF will create and will associate with the rule. The name can contain only alphanumeric characters (A-Z, a-z, 0-9); it can't contain whitespace.

3. For the first condition that you want to add to the rule, specify the following settings:
  - Choose whether you want AWS WAF to allow or block requests based on whether a web request does or does not match the settings in the condition.  
  
For this example, choose **does**.
  - Choose the type of condition that you want to add to the rule: an IP match set condition, a string match set condition, or a SQL injection match set condition.

For this example, choose **originate from IP addresses in**.

- Choose the condition that you want to add to the rule.

For this example, choose the IP match condition that you created in previous tasks.

4. Choose **Add another condition**.
5. Add the string match condition that you created earlier. Specify the following values:
  - **When a request does**
  - **match at least one of the filters in the string match condition**
  - Choose your string match condition.
6. Choose **Add another condition**.
7. Add the SQL injection match condition that you created earlier. Specify the following values:
  - **When a request does**
  - **match at least one of the filters in the SQL injection match condition**
  - Choose your SQL injection match condition.
8. Choose **Add another condition**.
9. Add the size constraint condition that you created earlier. Specify the following values:
  - **When a request does**
  - **match at least one of the filters in the size constraint condition**
  - Choose your size constraint condition.
10. Choose **Create**.

## Step 8: Add the Rule to a Web ACL

When you add the rule to a web ACL, you specify the following settings:

- The action that you want AWS WAF to take on web requests that match all of the conditions in the rule: allow, block, or count the requests.
- The default action for the web ACL. This is the action that you want AWS WAF to take on web requests that *do not* match all of the conditions in the rule: allow or block the requests.

You can add more than one rule to a web ACL. If a web ACL contains more than one rule, AWS WAF inspects web requests based on the conditions in each rule in the order that the rules are listed. For example, if a web request matches one rule that allows requests and another rule that blocks requests, AWS WAF will either allow or block the request depending on which rule is listed first.

### Note

For more information about rules, see [Working with Web ACLs \(p. 59\)](#). For a list of limits on AWS WAF objects, such as the number of rules that you can create per AWS account, see [Limits \(p. 92\)](#).

### To add a rule to a web ACL

1. On the **Create rules** page of the wizard, under **Add rules to a web ACL**, the rule that you created in a preceding task is already selected because it's the only rule you have.

When you have more than one rule, you choose the rule that you want to add from the Rules list, and choose **Add rule to web ACL**.

2. For the rule that you added to the web ACL in the preceding step, choose whether you want AWS WAF to allow, block, or count requests that match all of the conditions in the rule.

For this example, choose **Block**.

3. Choose the default action for the web ACL. AWS WAF takes this action on web requests that do not match all of the conditions in the rule.

For this example, choose **Allow all requests that don't match any rules**.

4. Choose **Next**.

## Step 9: Associate a Web ACL with a CloudFront Distribution

The final step is to associate the web ACL with the CloudFront distribution for which you want AWS WAF to inspect web requests.

### To choose the AWS resource for which you want AWS WAF to inspect requests

1. On the **Choose AWS resource** page, in the **Resource** list, choose the CloudFront distribution that you want to associate this web ACL with.
2. Choose **Review and create**.
3. Review the settings for your web ACL, and choose **Confirm and create**.

AWS WAF will now start blocking CloudFront web requests that match all of the following conditions:

- The value of the `User-Agent` header is `BadBot`
- The requests originate from IP addresses in the range 192.0.2.0-192.0.2.255
- The requests appear to include malicious SQL code in the query string

AWS WAF will allow CloudFront to respond to any requests that don't meet all three of these conditions.

## Step 10: Clean Up Your Resources

You've now successfully completed the tutorial. To prevent your account from accruing additional AWS WAF charges, you should clean up the AWS WAF objects that you created. Alternatively, you can change the configuration to match the web requests that you really want to allow, block, and count.

### Note

AWS typically will bill you less than US\$0.25 per day for the resources that you create during this tutorial. When you're finished, we recommend that you delete the resources to prevent incurring unnecessary charges.

### **To delete the objects that AWS WAF charges for**

1. Disassociate your web ACL from your CloudFront distribution:
  - a. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
  - b. Choose the web ACL that you want to delete.
  - c. In the right pane, on the **Rules** tab, go to the **AWS resources using this web ACL** section. For the CloudFront distribution that you associated the web ACL with, choose the **x** in the **Type** column.
  
2. Remove the conditions from your rule:
  - a. In the navigation pane, choose **Rules**.
  - b. Choose the rule that you created during the tutorial.
  - c. Choose **Edit rule**.
  - d. Choose the **x** at the right end of each condition heading.
  - e. Choose **Update**.
  
3. Remove the rule from your web ACL, and delete the web ACL:
  - a. In the navigation pane, choose **Web ACLs**.
  - b. Choose the web ACL that you created during the tutorial.
  - c. On the **Rules** tab, choose **Edit web ACL**.
  - d. Choose the **x** at the right end of the rule heading.
  - e. Choose **Actions**, and then choose **Delete web ACL**.
  
4. Delete your rule:
  - a. In the navigation pane, choose **Rules**.
  - b. Choose the rule that you created during the tutorial.
  - c. Choose **Delete**.
  - d. In the **Delete** prompt, choose **Delete** again to confirm.

AWS WAF doesn't charge for conditions, but if you want to complete the cleanup, perform the following procedure to remove filters from conditions and delete the conditions.

### **To delete filters and conditions**

1. Delete the IP address range in your IP match condition, and delete the IP match condition:
  - a. In the navigation pane of the AWS WAF console, choose **IP addresses**.
  - b. Choose the IP match condition that you created during the tutorial.
  - c. Select the check box for the IP address range that you added.
  - d. Choose **Delete IP address or range**.
  - e. In the **IP match conditions** pane, choose **Delete**.
  - f. In the **Delete** prompt, choose **Delete** again to confirm.

2. Delete the filter in your SQL injection match condition, and delete the SQL injection match condition:
  - a. In the navigation pane, choose **SQL injection**.
  - b. Choose the SQL injection match condition that you created during the tutorial.
  - c. Select the check box for the filter that you added.
  - d. Choose **Delete filter**.
  - e. In the **SQL injection match conditions** pane, choose **Delete**.
  - f. In the **Delete** prompt, choose **Delete** again to confirm.
  
3. Delete the filter in your string match condition, and delete the string match condition:
  - a. In the navigation pane, choose **String matching**.
  - b. Choose the string match condition that you created during the tutorial.
  - c. Select the check box for the filter that you added.
  - d. Choose **Delete filter**.
  - e. In the **String match conditions** pane, choose **Delete**.
  - f. In the **Delete** prompt, choose **Delete** again to confirm.
  
4. Delete the filter in your size constraint condition, and delete the size constraint condition:
  - a. In the navigation pane, choose **Size constraints**.
  - b. Choose the size constraint condition that you created during the tutorial.
  - c. Select the check box for the filter that you added.
  - d. Choose **Delete filter**.
  - e. In the **Size constraint conditions** pane, choose **Delete**.
  - f. In the **Delete** prompt, choose **Delete** again to confirm.

# Tutorials

---

This section contains tutorials that present complete end-to-end solutions for common tasks that you can perform in AWS WAF. They explain how to combine several AWS services to automatically configure AWS WAF in response to your CloudFront traffic. Their purpose is to provide general guidance. They are not intended for direct use in your production environment without careful review and adaptation to the unique aspects of your organization's environment.

## Tutorials

- [Tutorial: Quickly Setting Up AWS WAF Protection Against Common Attacks \(p. 17\)](#)
- [Tutorial: Blocking IP Addresses that Exceed Request Limits \(p. 23\)](#)
- [Tutorial: Blocking IP Addresses that Submit Bad Requests \(p. 29\)](#)

## Tutorial: Quickly Setting Up AWS WAF Protection Against Common Attacks

This tutorial shows you how to use [AWS CloudFormation](#) to quickly configure AWS WAF to protect against the following common attacks:

- **Cross-site scripting attacks** – Attackers sometimes insert scripts into web requests in an effort to exploit vulnerabilities in web applications. Cross-site scripting match conditions identify the parts of web requests, such as the URI or the query string, that you want AWS WAF to inspect for possible malicious scripts.
- **SQL injection attacks** – Attackers sometimes insert malicious SQL code into web requests in an effort to extract data from your database. SQL injection match conditions identify the part of web requests that you want AWS WAF to inspect for possible malicious SQL code.
- **Attacks from known bad IP addresses** – You can use IP match conditions to allow, block, or count web requests based on the IP addresses that the requests originate from. An IP match condition lists up to 1,000 IP addresses or IP address ranges that you specify.

## Topics

- [Solution Overview \(p. 18\)](#)
- [Step 1: Create an AWS CloudFormation Stack that Sets Up AWS WAF Protection Against Common Attacks \(p. 20\)](#)

- [Step 2: Associate a Web ACL with a CloudFront Distribution \(p. 33\)](#)
- [Step 3: \(Optional\) Add IP Addresses to the IP Match Condition \(p. 22\)](#)
- [Step 4: \(Optional\) Update the Web ACL to Block Large Bodies \(p. 22\)](#)
- [Step 5: \(Optional\) Delete Your AWS CloudFormation Stack \(p. 23\)](#)
- [Related Resources \(p. 36\)](#)

## Solution Overview

AWS CloudFormation uses a template to set up the following AWS WAF conditions, rules, and a web ACL.

### Conditions

AWS CloudFormation creates the following conditions.

#### IP Match Condition

Filters requests that come from known bad IP addresses. This lets you easily add IPs to a list to block access to your website. You might want to do this if you're receiving a lot of bad requests from one or more IP addresses. If you want to allow, block, or count requests based on the IP addresses that the requests come from, see [Step 3: \(Optional\) Add IP Addresses to the IP Match Condition \(p. 22\)](#) later in this tutorial.

The name of the condition is `prefixManualBlockSet` where `prefix` is the name that you specify for the web ACL when you create the AWS CloudFormation stack.

#### Size Constraint Condition

Filters requests for which the body is longer than 8,192 bytes. AWS WAF evaluates only the first 8,192 bytes of the request part that you specify in a filter. If valid request bodies never exceed 8,192 bytes, you can use a size constraint condition to catch malicious requests that might otherwise slip through.

For this tutorial, AWS CloudFormation configures AWS WAF only to count requests that have a body longer than 8,192 bytes, not to block them. If the body in your requests never exceeds that length, you can change the configuration to block requests that have longer bodies. For information about how to view the count of requests that exceed 8,192 bytes and how to change the web ACL to block requests that contain bodies larger than 8,192 bytes, see [Step 4: \(Optional\) Update the Web ACL to Block Large Bodies \(p. 22\)](#).

The name of the condition is `prefixLargeBodyMatch` where `prefix` is the name that you specify for the web ACL when you create the AWS CloudFormation stack.

#### SQL Injection Condition

Filters requests that contain possible malicious SQL code. The condition includes filters that evaluate the following parts of requests:

- Query string (URL decode transformation)
- URI (URL decode transformation)
- Body (URL decode transformation)
- Body (HTML decode transformation)

The name of the condition is `prefixSqliMatch` where `prefix` is the name that you specify for the web ACL when you create the AWS CloudFormation stack.

#### Cross-site Scripting Condition

Filters requests that contain possible malicious scripts. The condition includes filters that evaluate the following parts of requests:

- Query string (URL decode transformation)

- URI (URL decode transformation)
- Body (URL decode transformation)
- Body (HTML decode transformation)

The name of the condition is `prefixXssMatch` where `prefix` is the name that you specify for the web ACL when you create the AWS CloudFormation stack.

## Rules

When you create the AWS CloudFormation stack, AWS CloudFormation creates the following rules and adds the corresponding condition to each rule.

### `prefixManualIPBlockRule`

AWS CloudFormation adds the `prefixManualBlockSet` condition to this rule.

### `prefixSizeMatchRule`

AWS CloudFormation adds the `prefixLargeBodyMatch` condition to this rule.

### `prefixSqliRule`

AWS CloudFormation adds the `prefixSqliMatch` condition to this rule.

### `prefixXssRule`

AWS CloudFormation adds the `prefixXssMatch` condition to this rule.

## Web ACL

AWS CloudFormation creates a web ACL that has the name that you specify when you create the AWS CloudFormation stack. The web ACL contains the following rules with the specified settings:

### `prefixManualIPBlockRule`

By default, the condition in this rule doesn't contain any IP addresses. If you want to allow, block, or count requests based on the IP addresses that the requests come from, see [Step 3: \(Optional\) Add IP Addresses to the IP Match Condition \(p. 22\)](#) later in this tutorial.

### `prefixSizeMatchRule`

By default, AWS WAF counts requests for which the body is longer than 8,192 bytes.

### `prefixSqliRule`

AWS WAF blocks requests based on the settings in this rule.

### `prefixXssRule`

AWS WAF blocks requests based on the settings in this rule.

## Requirements

This tutorial assumes that you already have a CloudFront distribution that you use to deliver content for your web application. If you don't have a CloudFront distribution, see [Creating or Updating a Web Distribution Using the CloudFront Console](#) in the *Amazon CloudFront Developer Guide*. This tutorial also uses AWS CloudFormation to simplify the provisioning process. For more information, see the [AWS CloudFormation User Guide](#).

## Estimated Time

15 minutes if you already have a CloudFront distribution, 30 minutes if you need to create a CloudFront distribution.



## Estimated Cost

- **AWS WAF**

The total cost is \$9.00 per month plus the charge for the requests that AWS WAF inspects:

- \$5.00 per month per web ACL (the tutorial creates one web ACL)
- \$1.00 per month per rule (x4 for the two rules that AWS CloudFormation creates for this tutorial)
- \$0.60 per million requests
- **CloudFront** – You don't incur any additional CloudFront charges for this solution. For more information, see [Amazon CloudFront Pricing](#).

## Step 1: Create an AWS CloudFormation Stack that Sets Up AWS WAF Protection Against Common Attacks

In the following procedure, you use a AWS CloudFormation template to create a stack that sets up AWS WAF protection against common attacks.

### Important

You begin to incur charges for the different services when you create the AWS CloudFormation stack that deploys this solution. Charges continue to accrue until you delete the AWS CloudFormation stack. For more information, see [Step 5: \(Optional\) Delete Your AWS CloudFormation Stack \(p. 23\)](#).

### To create an AWS CloudFormation stack for blocking IP addresses that submit bad requests

1. To start the wizard that creates an AWS CloudFormation stack, choose the link for the region in which you want to create AWS resources:
  - [Create a stack in US East \(N. Virginia\)](#)
  - [Create a stack in US West \(Oregon\)](#)
  - [Create a stack in EU \(Ireland\)](#)
  - [Create a stack in Asia Pacific \(Tokyo\)](#)
2. If you are not already signed in to the AWS Management Console, sign in when prompted.
3. On the **Select Template** page, choose **Specify an Amazon S3 template URL**. For the template URL, enter `https://s3.amazonaws.com/cloudformation-examples/community/common-attacks.json`.
4. Choose **Next**.
5. On the **Specify Details** page, specify the following values:

#### Stack Name

You can use the default name (**CommonAttackProtection**) or you can change the name. The stack name must not contain spaces and must be unique within your AWS account.

#### Name

Specify a name for the web ACL that AWS CloudFormation will create. The name that you specify is also used as a prefix for the conditions and rules that AWS CloudFormation will create, so you can easily find all of the related objects.

6. Choose **Next**.

7. (Optional) On the **Options** page, enter tags and advanced settings or leave the fields blank.
8. Choose **Next**.
9. On the **Review** page, review the configuration and then choose **Create**.

After you choose **Create**, AWS CloudFormation creates the AWS WAF resources identified in [Solution Overview \(p. 18\)](#).

## Step 2: Associate a Web ACL with a CloudFront Distribution

After AWS CloudFormation creates the stack, you need to associate the CloudFront distribution to activate AWS WAF and update your Amazon S3 bucket to enable event notification.

### Note

You can associate a web ACL with as many CloudFront distributions as you want, but you can associate only one web ACL with a given distribution.

### To associate a web ACL with a CloudFront distribution

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to associate with a CloudFront distribution.
4. On the **Rules** tab, under **AWS resources using this web ACL**, choose **Add association**.
5. When prompted, use the **Resource** list to choose the distribution that you want to associate this web ACL with.
6. Choose **Add**.
7. To associate this web ACL with additional CloudFront distributions, repeat steps 4 through 6.

If you already have an Amazon S3 bucket for CloudFront access logs (if you selected **no** for **Create CloudFront Access Log Bucket** in the preceding procedure), enable Amazon S3 event notification to trigger the Lambda function when a new log file is added to the bucket. For more information, see [Enabling Event Notifications](#) in the *Amazon Simple Storage Service Console User Guide*.

### Note

If you chose to have AWS CloudFormation create the bucket for you, AWS CloudFormation also enabled event notifications for the bucket.

### To enable Amazon S3 event notification

1. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
2. Choose the bucket that you want to use for CloudFront access logs.
3. Choose **Properties**, and expand **Events**.
4. Specify the following values:

#### Name

Type a name for the event, such as **LambdaNotificationsForWAFBadRequests**. The name cannot contain spaces.

#### Events

Select **ObjectCreated (All)**.

#### Prefix

Leave the field empty.

**Suffix**

Type **gz**.

**Send To**

Select **Lambda function**.

**Lambda function**

Choose **BadBehavingIP** or the name that you specified for your AWS CloudFormation stack.

5. Choose **Save**.

## Step 3: (Optional) Add IP Addresses to the IP Match Condition

When you created the AWS CloudFormation stack, AWS CloudFormation created an IP match condition for you, added it to a rule, added the rule to a web ACL, and configured the web ACL to block requests based on IP addresses. The IP match condition doesn't include any IP addresses, though. If you want to block requests based on IP addresses, perform the following procedure.

### To edit AWS CloudFormation parameter values

1. Open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **IP addresses**.
3. In the **IP match conditions** pane, choose the IP match condition that you want to edit.
4. To add an IP address range:
  - a. In the right pane, choose **Add IP address or range**.
  - b. Type an IP address or range by using CIDR notation. Here are two examples:
    - To specify the IP address 192.0.2.44, type **192.0.2.44/32**.
    - To specify the range of IP addresses from 192.0.2.0 to 192.0.2.255, type **192.0.2.0/24**.

AWS WAF supports /8, /16, /24, and /32 IP address ranges. For more information about CIDR notation, see the Wikipedia entry [Classless Inter-Domain Routing](#).

**Note**

AWS WAF currently supports only IPv4 IP addresses.

- c. To add more IP addresses, choose **Add another IP address** and type the value.
- d. Choose **Add**.

## Step 4: (Optional) Update the Web ACL to Block Large Bodies

When you created the AWS CloudFormation stack, AWS CloudFormation created a size constraint condition that filters requests that have request bodies longer than 8,192 bytes. It also added the condition to a rule, and added the rule to the web ACL. However, AWS CloudFormation configured the web ACL to count requests based on that limit, not to block requests, because we didn't know whether you have any valid requests that are longer than 8,192 bytes.

If you want to block requests that are longer than 8,192 bytes, perform the following procedure.

### To change the action for a rule in a web ACL

1. Open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to edit.
4. In the right pane, choose the **Rules** tab.
5. Choose **Edit Web ACL**.
6. To change the action for the `prefixLargeBodyMatchRule`, choose the preferred option. (`prefix` is the value that you specified for the name of the web ACL.)
7. Choose **Save changes**.

## Step 5: (Optional) Delete Your AWS CloudFormation Stack

If you want to stop protecting from common attacks as described in [Solution Overview \(p. 18\)](#), delete the AWS CloudFormation stack that you created in [Step 1: Create an AWS CloudFormation Stack that Sets Up AWS WAF Protection Against Common Attacks \(p. 20\)](#). This deletes the AWS WAF resources that AWS CloudFormation created and stops the AWS charges for those resources.

### To delete an AWS CloudFormation stack

1. Sign in to the AWS Management Console and open the AWS CloudFormation console at <https://console.aws.amazon.com/cloudformation/>.
2. Select the check box for the stack; the default name is **CommonAttackProtection**.
3. Choose **Delete Stack**.
4. Choose **Yes, Delete** to confirm.
5. To track the progress of the stack deletion, select the check box for the stack, and choose the **Events** tab in the bottom pane.

## Related Resources

For AWS WAF samples, including Lambda functions, AWS CloudFormation templates, and SDK usage examples, go to GitHub at:

- <https://github.com/awslabs/aws-waf-sample>

## Tutorial: Blocking IP Addresses that Exceed Request Limits


Using [AWS Lambda](#), you can set a threshold of how many requests per minute your web application can serve. If users (based on IP addresses) exceed this request rate, Lambda will automatically update your AWS WAF rules to block IP addresses and specify for how long requests from those IP addresses should be blocked.

This tutorial shows you how to use an [AWS CloudFormation](#) template to specify the request threshold and time to block requests. The tutorial also uses CloudFront [access logs](#) (stored in [Amazon S3](#)) to count requests as they are served by [CloudFront](#) and by [Amazon CloudWatch](#) metrics.

### Topics

- [Solution Overview](#) (p. 24)
- [Step 1: Create an AWS CloudFormation Stack for Rate-Based Blocking](#) (p. 25)
- [Step 2: Associate a Web ACL with a CloudFront Distribution](#) (p. 26)
- [Step 3: \(Optional\) Edit AWS CloudFormation Parameter Values](#) (p. 28)
- [Step 4: \(Optional\) Test Your Thresholds and IP Rules](#) (p. 28)
- [Step 5: \(Optional\) Delete Your AWS CloudFormation Stack](#) (p. 29)
- [Related Resources](#) (p. 36)

## Solution Overview



1. As CloudFront receives requests on behalf of your web application, it sends access logs to an Amazon S3 bucket that contains detailed information about the requests.
2. For every new access log stored in the Amazon S3 bucket, a Lambda function is triggered.
3. The Lambda function analyzes which IP addresses have made more requests than the defined threshold and adds those IP addresses to an AWS WAF block list. AWS WAF blocks those IP addresses for a period of time that you define. After this blocking period has expired, AWS WAF allows those IP addresses to access your application again, but continues to monitor the requests from those IP addresses.
4. The Lambda function publishes execution metrics in CloudWatch, such as the number of requests analyzed and IP addresses blocked.

The AWS CloudFormation template will create a web access control list (web ACL) and three separate rules in AWS WAF that will block and monitor requests from IP addresses, depending on the settings that you configure during the tutorial. The three rules are defined here:

- **Auto Block** – This rule adds IP addresses that exceed the request-per-minute limit. New requests from those IP addresses are blocked until Lambda removes the IP addresses from the block list after the specified expiration period. The default is four hours.

**AWS WAF Developer Guide**  
**Step 1: Create an AWS CloudFormation Stack for**  
**Rate-Based Blocking**

---

- **Manual Block** – This rule adds IP addresses manually to the auto-block list. The IP addresses are permanently blocked; they can access the web application only if you remove them from the block list. You can use this list to block known bad IP addresses or IP addresses that are frequently added to the auto-block rule.
- **Auto Count** – This is a quarantine rule: the requests are not blocked, but you track in near real-time the number of requests from previously blocked IP addresses. This rule gives you visibility into an IP address's behavior after being removed from the auto-block rule.

**Requirements:** This tutorial assumes that you already have a CloudFront distribution that you use to deliver content for your web application. If you don't have a CloudFront distribution, see [Creating or Updating a Web Distribution Using the CloudFront Console](#) in the *Amazon CloudFront Developer Guide*. This tutorial also uses AWS CloudFormation to simplify the provisioning process. For more information, see the [AWS CloudFormation User Guide](#).

**Estimated time:** 15 minutes if you already have a CloudFront distribution, 30 minutes if you need to create a CloudFront distribution.

**Estimated cost:**

- **AWS WAF**
  - \$5.00 per month per web ACL (the tutorial creates one web ACL)
  - \$1.00 per month per rule (x3 for the three rules that AWS CloudFormation creates for this tutorial)
  - \$0.60 per million requests
- **AWS Lambda** – Each new CloudFront access log represents a new request and triggers the Lambda function that is created by this tutorial. Lambda charges include:
  - **Requests** – The first million requests are free, then Lambda charges \$0.20 per million requests. CloudFront delivers access logs for a distribution up to several times an hour.
  - **Memory used per second** – \$0.00001667 per GB of memory used per second.
- **Amazon S3** – Amazon S3 charges for storing CloudFront access logs. The size of the logs and, therefore, the charge for storage depends on the number of requests that CloudFront receives for your objects. For more information, see [Amazon S3 Pricing](#).
- **CloudFront** – You don't incur any additional CloudFront charges for this solution. For more information, see [Amazon CloudFront Pricing](#).

## Step 1: Create an AWS CloudFormation Stack for Rate-Based Blocking

In the following procedure, you use a AWS CloudFormation template to create a stack that launches the AWS resources required by Lambda, CloudFront, Amazon S3, AWS WAF, and CloudWatch.

**Important**

You begin to incur charges for the different services when you create the AWS CloudFormation stack that deploys this solution. Charges continue to accrue until you delete the AWS CloudFormation stack. For more information, see [Step 5: \(Optional\) Delete Your AWS CloudFormation Stack](#) (p. 29).

**To create an AWS CloudFormation stack for rate-based blocking**

1. To start the wizard that creates an AWS CloudFormation stack, choose the link for the region in which you want to create AWS resources:
  - [Create a stack in US East \(N. Virginia\)](#)
  - [Create a stack in US West \(Oregon\)](#)

**AWS WAF Developer Guide**  
**Step 2: Associate a Web ACL with a CloudFront**  
**Distribution**

---

- [Create a stack in EU \(Ireland\)](#)
  - [Create a stack in Asia Pacific \(Tokyo\)](#)
2. If you are not already signed in to the AWS Management Console, sign in when prompted.
  3. On the **Select Template** page, the selected URL automatically appears under **Specify an Amazon S3 template URL**. Choose **Next**.
  4. On the **Specify Details** page, specify the following values:

**Stack Name**

You can use the default name (**RateBasedBL**) or you can change the name. The stack name must not contain spaces and must be unique within your AWS account.

**Create CloudFront Access Log Bucket**

Select **yes** to create a new Amazon S3 bucket for CloudFront access logs, or select **no** if you already have an Amazon S3 bucket for CloudFront access logs.

**CloudFront Access Log Bucket Name**

Type the name of the Amazon S3 bucket where you want CloudFront to put access logs. Leave this field empty if you selected **no** for **Create CloudFront Access Log Bucket**.

**Request Threshold**

Type the maximum number of requests that can be made from an IP address per minute without being blocked. The default is 400.

**WAF Block Period**

Specify how long (in minutes) an IP address should be blocked after crossing the threshold. The default is 240 minutes (four hours).

**WAF Quarantine Period**

Specify how long (in minutes) AWS WAF should monitor IP addresses after AWS WAF has stopped blocking them. The default is 240 minutes.

5. Choose **Next**.
6. (Optional) On the **Options** page, you can enter tags and advanced settings, or you can leave the fields blank. Choose **Next**.
7. On the **Review** page, select the **I acknowledge** check box, and then choose **Create**.

After you choose **Create**, AWS CloudFormation creates the AWS resources necessary to run the solution:

- Lambda function
- AWS WAF web ACL (named **Malicious Requesters**) with the necessary rules configured
- CloudWatch custom metric
- Amazon S3 bucket with the name that you specified in the **CloudFront Access Log Bucket Name** field in step 6, if you selected **yes** for **Create CloudFront Access Log Bucket**

## Step 2: Associate a Web ACL with a CloudFront Distribution

After AWS CloudFormation creates the stack, you need to associate the CloudFront distribution to activate AWS WAF and update your Amazon S3 bucket to enable event notification.

**AWS WAF Developer Guide**  
**Step 2: Associate a Web ACL with a CloudFront Distribution**

---

**Note**

If you're already using AWS WAF to monitor CloudFront requests and if logging is already enabled for the distribution that you're monitoring, you can skip the first procedure.

**Note**

You can associate a web ACL with as many CloudFront distributions as you want, but you can associate only one web ACL with a given distribution.

**To associate a web ACL with a CloudFront distribution**

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to associate with a CloudFront distribution.
4. On the **Rules** tab, under **AWS resources using this web ACL**, choose **Add association**.
5. When prompted, use the **Resource** list to choose the distribution that you want to associate this web ACL with.
6. Choose **Add**.
7. To associate this web ACL with additional CloudFront distributions, repeat steps 4 through 6.

If you already have an Amazon S3 bucket for CloudFront access logs (if you selected **no** for **Create CloudFront Access Log Bucket** in the preceding procedure), enable Amazon S3 event notification to trigger the Lambda function when a new log file is added to the bucket. For more information, see [Enabling Event Notifications](#) in the *Amazon Simple Storage Service Console User Guide*.

**Note**

If you chose to have AWS CloudFormation create the bucket for you, AWS CloudFormation also enabled event notifications for the bucket.

**To enable Amazon S3 event notification**

1. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
2. Choose the bucket that you want to use for CloudFront access logs.
3. Choose **Properties**, and expand **Events**.
4. Specify the following values:

**Name**

Type a name for the event, such as **LambdaNotificationsForWAFBadRequests**. The name cannot contain spaces.

**Events**

Select **ObjectCreated (All)**.

**Prefix**

Leave the field empty.

**Suffix**

Type **gz**.

**Send To**

Select **Lambda function**.

**Lambda function**

Choose **BadBehavingIP** or the name that you specified for your AWS CloudFormation stack.

5. Choose **Save**.



## Step 3: (Optional) Edit AWS CloudFormation Parameter Values

If you want to change the parameters after you create the AWS CloudFormation stack—for example, if you want to change the threshold value or how long IPs are blocked—you can update the AWS CloudFormation stack.

### To edit AWS CloudFormation parameter values

1. Open the AWS CloudFormation console at <https://console.aws.amazon.com/cloudformation/>.
2. In the list of stacks, choose the running stack that you want to update, which is **RateBasedBL** if you accepted the default value when you created the stack.
3. Choose **Actions**, and then choose **Update Stack**.
4. On the **Select Template** page, select **Use current template**, and then choose **Next**.
5. On the **Specify Details** page, change the values of **Rate-Based Blacklisting Parameters** as applicable:

#### Request Threshold

Type the new maximum number of requests that can be made per minute without being blocked.

#### WAF Block Period

Specify the new value of how long (in minutes) you want AWS WAF to block the IP address after the number of requests from that IP address exceed the value of **Request Threshold**.

#### WAF Quarantine Period

Specify the new value of how long (in minutes) you want AWS WAF to monitor the IP address after AWS WAF has stopped blocking it.

6. On the **Options** page, choose **Next**.
7. On the **Review** page, select the **I acknowledge** check box, and then choose **Update**.

AWS CloudFormation will update the stack to reflect the new values of the parameters.

## Step 4: (Optional) Test Your Thresholds and IP Rules

To test your solution, you can wait until CloudFront generates a new access log file, or you can simulate this process by uploading a sample access log into the Amazon S3 bucket that you specified for receiving log files.

### To test your thresholds and IP rules

1. Download the sample CloudFront [access log file](#) from the AWS website.
2. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
3. Choose the Amazon S3 bucket that you're using for CloudFront access logs for this tutorial.
4. Choose **Upload**.
5. Choose **Add Files**, choose the sample access log file, and choose **Start Upload**.

After the upload completes, perform the following procedure to confirm that the IP addresses were populated automatically in the AWS WAF **Auto Block** rule. Lambda will take a few seconds to process the log file and update the rule.

### To review IP addresses in the Auto Block rule

1. Open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the left pane, choose **Rules**.
3. Choose the **Auto Block** rule.
4. Confirm that the **Auto Block** rule includes an IP match condition that contains IP addresses.

## Step 5: (Optional) Delete Your AWS CloudFormation Stack

If you want to stop blocking IP addresses based on the rate at which they submit requests, delete the AWS CloudFormation stack that you created in [Step 1: Create an AWS CloudFormation Stack for Rate-Based Blocking \(p. 25\)](#). This deletes the AWS resources that AWS CloudFormation created and stops the AWS charges for those resources.

### To delete an AWS CloudFormation stack

1. Sign in to the AWS Management Console and open the AWS CloudFormation console at <https://console.aws.amazon.com/cloudformation/>.
2. Select the check box for the stack; the default name is **RateBasedBL**.
3. Choose **Delete Stack**.
4. Choose **Yes, Delete** to confirm.
5. To track the progress of the stack deletion, select the check box for the stack, and choose the **Events** tab in the bottom pane.

## Related Resources

For AWS WAF samples, including Lambda functions, AWS CloudFormation templates, and SDK usage examples, go to GitHub at:

- <https://github.com/awslabs/aws-waf-sample>

## Tutorial: Blocking IP Addresses that Submit Bad Requests

Using [AWS Lambda](#), you can set a threshold of how many bad requests per minute your web application will tolerate from a given IP address. A bad request is one for which your CloudFront origin returns one of the following HTTP 40x status codes:

- 400, Bad Request
- 403, Forbidden
- 404, Not Found
- 405, Method Not Allowed


If users (based on IP addresses) exceed this error code threshold, Lambda will automatically update your AWS WAF rules to block IP addresses and specify for how long requests from those IP addresses should be blocked.

This tutorial shows you how to use an [AWS CloudFormation](#) template to specify the request threshold and time to block requests. The tutorial also uses CloudFront [access logs](#) (stored in [Amazon S3](#)) to count requests as they are served by [CloudFront](#) and by [Amazon CloudWatch](#) metrics.

### Topics

- [Solution Overview](#) (p. 30)
- [Step 1: Create an AWS CloudFormation Stack for Blocking IP Addresses that Submit Bad Requests](#) (p. 31)
- [Step 2: Associate a Web ACL and a CloudFront Distribution](#) (p. 33)
- [Step 2: Associate a Web ACL with a CloudFront Distribution](#) (p. 33)
- [Step 3: \(Optional\) Edit AWS CloudFormation Parameter Values](#) (p. 34)
- [Step 4: \(Optional\) Test Your Thresholds and IP Rules](#) (p. 35)
- [Step 5: \(Optional\) Delete Your AWS CloudFormation Stack](#) (p. 35)
- [Related Resources](#) (p. 36)

## Solution Overview



1. As CloudFront receives requests on behalf of your web application, it sends access logs to an Amazon S3 bucket that contains detailed information about the requests.
2. For every new access log stored in the Amazon S3 bucket, a Lambda function is triggered. The Lambda function parses the log files and looks for requests that resulted in error codes 400, 403, 404, and 405. The function then counts the number of bad requests and temporarily stores results in `current_outstanding_requesters.json` in the Amazon S3 bucket that you're using for access logs.

**AWS WAF Developer Guide**  
**Step 1: Create an AWS CloudFormation Stack for Blocking IP Addresses that Submit Bad Requests**

---

3. The Lambda function updates AWS WAF rules to block the IP addresses that are listed in `current_outstanding_requesters.json` for a period of time that you specify. After this blocking period has expired, AWS WAF allows those IP addresses to access your application again, but continues to monitor the requests from those IP addresses.
4. The Lambda function publishes execution metrics in CloudWatch, such as the number of requests analyzed and IP addresses blocked.

The AWS CloudFormation template will create a web access control list (web ACL) and two separate rules in AWS WAF that will block and monitor requests from IP addresses, depending on the settings that you configure during the tutorial. The two rules are defined here:

- **Auto Block** – This rule adds IP addresses that exceed the request-per-minute limit. New requests from those IP addresses are blocked until Lambda removes the IP addresses from the block list after the specified expiration period. The default is four hours.
- **Manual Block** – This rule adds IP addresses manually to the auto-block list. The IP addresses are permanently blocked; they can access the web application only if you remove them from the block list. You can use this list to block known bad IP addresses or IP addresses that are frequently added to the auto-block rule.

**Requirements:** This tutorial assumes that you already have a CloudFront distribution that you use to deliver content for your web application. If you don't have a CloudFront distribution, see [Creating or Updating a Web Distribution Using the CloudFront Console](#) in the *Amazon CloudFront Developer Guide*. This tutorial also uses AWS CloudFormation to simplify the provisioning process. For more information, see the [AWS CloudFormation User Guide](#).

**Estimated time:** 15 minutes if you already have a CloudFront distribution, 30 minutes if you need to create a CloudFront distribution.

**Estimated cost:**

- **AWS WAF**
  - \$5.00 per month per web ACL (the tutorial creates one web ACL)
  - \$1.00 per month per rule (x2 for the two rules that AWS CloudFormation creates for this tutorial)
  - \$0.60 per million requests
- **AWS Lambda** – Each new CloudFront access log represents a new request and triggers the Lambda function that is created by this tutorial. Lambda charges include:
  - **Requests** – The first million requests are free, then Lambda charges \$0.20 per million requests. CloudFront delivers access logs for a distribution up to several times an hour.
  - **Memory used per second** – \$0.00001667 per GB of memory used per second.
- **Amazon S3** – Amazon S3 charges for storing CloudFront access logs. The size of the logs and, therefore, the charge for storage depends on the number of requests that CloudFront receives for your objects. For more information, see [Amazon S3 Pricing](#).
- **CloudFront** – You don't incur any additional CloudFront charges for this solution. For more information, see [Amazon CloudFront Pricing](#).

## Step 1: Create an AWS CloudFormation Stack for Blocking IP Addresses that Submit Bad Requests

In the following procedure, you use a AWS CloudFormation template to create a stack that launches the AWS resources required by Lambda, CloudFront, Amazon S3, AWS WAF, and CloudWatch.

### **Important**

You begin to incur charges for the different services when you create the AWS CloudFormation stack that deploys this solution. Charges continue to accrue until you delete the AWS CloudFormation stack. For more information, see [Step 5: \(Optional\) Delete Your AWS CloudFormation Stack](#) (p. 35).

### **To create an AWS CloudFormation stack for blocking IP addresses that submit bad requests**

1. To start the wizard that creates an AWS CloudFormation stack, choose the link for the region in which you want to create AWS resources:
  - [Create a stack in US East \(N. Virginia\)](#)
  - [Create a stack in US West \(Oregon\)](#)
  - [Create a stack in EU \(Ireland\)](#)
  - [Create a stack in Asia Pacific \(Tokyo\)](#)
2. If you are not already signed in to the AWS Management Console, sign in when prompted.
3. On the **Select Template** page, the selected URL automatically appears under **Specify an Amazon S3 template URL**. Choose **Next**.
4. On the **Specify Details** page, specify the following values:

#### **Stack Name**

You can use the default name (**BadBehavingIP**) or you can change the name. The stack name must not contain spaces and must be unique within your AWS account.

#### **Create CloudFront Access Log Bucket**

Select **yes** to create a new Amazon S3 bucket for CloudFront access logs, or select **no** if you already have an Amazon S3 bucket for CloudFront access logs.

#### **CloudFront Access Log Bucket Name**

Type the name of the Amazon S3 bucket where you want CloudFront to put access logs. Leave this field empty if you selected **no** for **Create CloudFront Access Log Bucket**.

#### **Request Threshold**

Type the maximum number of requests that can be made from an IP address per minute without being blocked. The default is 400.

#### **WAF Block Period**

Specify how long (in minutes) an IP address should be blocked after crossing the threshold. The default is 240 minutes (four hours).

5. Choose **Next**.
6. (Optional) On the **Options** page, enter tags and advanced settings or leave the fields blank.
7. Choose **Next**.
8. On the **Review** page, select the **I acknowledge** check box, and then choose **Create**.

After you choose **Create**, AWS CloudFormation creates the AWS resources necessary to run the solution:

- Lambda function
- AWS WAF web ACL (named **Malicious Requesters**) with the necessary rules configured
- CloudWatch custom metric
- Amazon S3 bucket with the name that you specified in the **CloudFront Access Log Bucket Name** field in step 6, if you selected **yes** for **Create CloudFront Access Log Bucket**

## Step 2: Associate a Web ACL and a CloudFront Distribution

After AWS CloudFormation creates the stack, you need to associate the CloudFront distribution to activate AWS WAF and update your Amazon S3 bucket to enable event notification.

### Note

You can associate a web ACL with as many CloudFront distributions as you want, but you can associate only one web ACL with a given distribution.

### To associate a web ACL with a CloudFront distribution

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to associate with a CloudFront distribution.
4. On the **Rules** tab, under **AWS resources using this web ACL**, choose **Add association**.
5. When prompted, use the **Resource** list to choose the distribution that you want to associate this web ACL with.
6. Choose **Add**.
7. To associate this web ACL with additional CloudFront distributions, repeat steps 4 through 6.

## Step 2: Associate a Web ACL with a CloudFront Distribution

After AWS CloudFormation creates the stack, you need to associate the CloudFront distribution to activate AWS WAF and update your Amazon S3 bucket to enable event notification.

### Note

If you're already using AWS WAF to monitor CloudFront requests and if logging is already enabled for the distribution that you're monitoring, you can skip the first procedure.

### Note

You can associate a web ACL with as many CloudFront distributions as you want, but you can associate only one web ACL with a given distribution.

### To associate a web ACL with a CloudFront distribution

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to associate with a CloudFront distribution.
4. On the **Rules** tab, under **AWS resources using this web ACL**, choose **Add association**.
5. When prompted, use the **Resource** list to choose the distribution that you want to associate this web ACL with.
6. Choose **Add**.
7. To associate this web ACL with additional CloudFront distributions, repeat steps 4 through 6.

If you already have an Amazon S3 bucket for CloudFront access logs (if you selected **no** for **Create CloudFront Access Log Bucket** in the preceding procedure), enable Amazon S3 event notification to trigger the Lambda function when a new log file is added to the bucket. For more information, see [Enabling Event Notifications](#) in the *Amazon Simple Storage Service Console User Guide*.

**Note**

If you chose to have AWS CloudFormation create the bucket for you, AWS CloudFormation also enabled event notifications for the bucket.

**To enable Amazon S3 event notification**

1. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
2. Choose the bucket that you want to use for CloudFront access logs.
3. Choose **Properties**, and expand **Events**.
4. Specify the following values:

**Name**

Type a name for the event, such as **LambdaNotificationsForWAFBadRequests**. The name cannot contain spaces.

**Events**

Select **ObjectCreated (All)**.

**Prefix**

Leave the field empty.

**Suffix**

Type **gz**.

**Send To**

Select **Lambda function**.

**Lambda function**

Choose **BadBehavingIP** or the name that you specified for your AWS CloudFormation stack.

5. Choose **Save**.

## Step 3: (Optional) Edit AWS CloudFormation Parameter Values

If you want to change the parameters after you create the AWS CloudFormation stack—for example, if you want to change the threshold value or how long IPs are blocked—you can update the AWS CloudFormation stack.

**To edit AWS CloudFormation parameter values**

1. Open the AWS CloudFormation console at <https://console.aws.amazon.com/cloudformation/>.
2. In the list of stacks, choose the running stack that you want to update, which is **BadBehavingIP** if you accepted the default value when you created the stack.
3. Choose **Actions**, and then choose **Update Stack**.
4. On the **Select Template** page, select **Use current template**, and then choose **Next**.
5. On the **Specify Details** page, change the values of **Error Code Blacklisting Parameters** as applicable:

**Request Threshold**

Type the new maximum number of requests that can be made per minute without being blocked.

**WAF Block Period**

Specify the new value of how long (in minutes) you want AWS WAF to block the IP address after the number of requests from that IP address exceed the value of **Request Threshold**.

6. On the **Options** page, choose **Next**.

7. On the **Review** page, select the **I acknowledge** check box, and then choose **Update**.

AWS CloudFormation will update the stack to reflect the new values of the parameters.

## Step 4: (Optional) Test Your Thresholds and IP Rules

To test your solution, you can wait until CloudFront generates a new access log file, or you can simulate this process by uploading a sample access log into the Amazon S3 bucket that you specified for receiving log files.

### To test your thresholds and IP rules

1. Download the sample CloudFront [access log file](#) from the AWS website.
2. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
3. Choose the Amazon S3 bucket that you're using for CloudFront access logs for this tutorial.
4. Choose **Upload**.
5. Choose **Add Files**, choose the sample access log file, and choose **Start Upload**.

After the upload completes, perform the following procedure to confirm that the IP addresses were populated automatically in the AWS WAF **Auto Block** rule. Lambda will take a few seconds to process the log file and update the rule.

### To review IP addresses in the Auto Block rule

1. Open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the left pane, choose **Rules**.
3. Choose the **Auto Block** rule.
4. Confirm that the **Auto Block** rule includes an IP match condition that contains IP addresses.

## Step 5: (Optional) Delete Your AWS CloudFormation Stack

If you want to stop blocking IP addresses that submit bad requests, delete the AWS CloudFormation stack that you created in [Step 1: Create an AWS CloudFormation Stack for Blocking IP Addresses that Submit Bad Requests \(p. 31\)](#). This deletes the AWS resources that AWS CloudFormation created and stops the AWS charges for those resources.

### To delete an AWS CloudFormation stack

1. Sign in to the AWS Management Console and open the AWS CloudFormation console at <https://console.aws.amazon.com/cloudformation/>.
2. Select the check box for the stack; the default name is **BadBehavingIP**.
3. Choose **Delete Stack**.
4. Choose **Yes, Delete** to confirm.
5. To track the progress of the stack deletion, select the check box for the stack, and choose the **Events** tab in the bottom pane.



## Related Resources

For AWS WAF samples, including Lambda functions, AWS CloudFormation templates, and SDK usage examples, go to GitHub at:

- <https://github.com/awslabs/aws-waf-sample>

### Blog Tutorials

The following tutorial topics link out to the [AWS Security Blog](#).

- [How to Import IP Address Reputation Lists to Automatically Update AWS WAF IP Blacklists](#)
- [How to Reduce Security Threats and Operating Costs Using AWS WAF and Amazon CloudFront](#)
- [How to Prevent Hotlinking by Using AWS WAF, Amazon CloudFront, and Referer Checking](#)
- [How to Use AWS CloudFormation to Automate Your AWS WAF Configuration with Example Rules and Match Conditions](#)

# Creating and Configuring a Web Access Control List (Web ACL)

---

A web access control list (web ACL) gives you fine-grained control over the web requests that your AWS resources, such as Amazon CloudFront distributions, respond to. You can allow or block requests that originate from an IP address or a range of IP addresses, requests that contain a specified string in a particular part of requests, requests that exceed a specified length, requests that appear to contain malicious SQL code (known as SQL injection), requests that appear to contain malicious scripts (known as cross-site scripting), or any combination of these conditions.

To choose the requests that you want to allow to have access to your content or that you want to block, perform the following tasks:

1. Choose the default action, allow or block, for web requests that don't match any of the conditions that you specify. For more information, see [Deciding on the Default Action for a Web ACL \(p. 38\)](#).
2. Specify the conditions under which you want to allow or block requests:
  - To allow or block requests based on whether the requests appear to contain malicious scripts, create cross-site scripting match conditions. For more information, see [Working with Cross-site Scripting Match Conditions \(p. 38\)](#).
  - To allow or block requests based on the IP addresses that they originate from, create IP match conditions. For more information, see [Working with IP Match Conditions \(p. 42\)](#).
  - To allow or block requests based on whether the requests exceed a specified length, create size constraint conditions. For more information, see [Working with Size Constraint Conditions \(p. 44\)](#).
  - To allow or block requests based on whether the requests appear to contain malicious SQL code, create SQL injection match conditions. For more information, see [Working with SQL Injection Match Conditions \(p. 48\)](#).
  - To allow or block requests based on strings that appear in the requests, create string match conditions. For more information, see [Working with String Match Conditions \(p. 52\)](#).
3. Add the conditions to one or more rules. If you add more than one condition to the same rule, web requests must match all of the conditions for AWS WAF to allow or block requests based on the rule. For more information, see [Working with Rules \(p. 56\)](#).
4. Add the rules to a web ACL. For each rule, specify whether you want AWS WAF to allow or block requests based on the conditions that you added to the rule. If you add more than one rule to a web ACL, AWS WAF evaluates the rules in the order that they're listed in the web ACL. For more information, see [Working with Web ACLs \(p. 59\)](#).

### Topics

- [Deciding on the Default Action for a Web ACL \(p. 38\)](#)
- [Working with Cross-site Scripting Match Conditions \(p. 38\)](#)
- [Working with IP Match Conditions \(p. 42\)](#)
- [Working with Size Constraint Conditions \(p. 44\)](#)
- [Working with SQL Injection Match Conditions \(p. 48\)](#)
- [Working with String Match Conditions \(p. 52\)](#)
- [Working with Rules \(p. 56\)](#)
- [Working with Web ACLs \(p. 59\)](#)

## Deciding on the Default Action for a Web ACL

When you create and configure a web ACL, the first and most important decision that you need to make is whether the default action should be for AWS WAF to allow web requests or to block web requests. The default action indicates what you want AWS WAF to do after it has inspected a web request for all of the conditions that you have specified, and the web request hasn't matched any of those conditions:

- **Allow** – If you want to allow most users to access your website, but you want to block access to attackers whose requests are originating from specified IP addresses, or whose requests appear to contain malicious SQL code or specified values, choose **Allow** for the default action.
- **Block** – If you want to prevent most would-be users from accessing your website, but you want to allow access to users whose requests are originating from specified IP addresses, or whose requests contain specified values, choose **Block** for the default action.

Many decisions that you make after you've decided on a default action depend on whether you want to allow or block most web requests. For example, if you want to *allow* most requests, then the match conditions that you create will generally specify the web requests that you want to *block*, such as:

- Requests that originate from IP addresses that are making an unreasonable number of requests
- Requests that include fake values in the **User-Agent** header
- Requests that appear to include malicious SQL code

## Working with Cross-site Scripting Match Conditions

Attackers sometimes insert scripts into web requests in an effort to exploit vulnerabilities in web applications. You can create one or more cross-site scripting match conditions to identify the parts of web requests, such as the URI or the query string, that you want AWS WAF to inspect for possible malicious scripts. Later in the process, when you create a web ACL, you specify whether to allow or block requests that appear to contain malicious scripts.

### Topics

- [Creating Cross-site Scripting Match Conditions \(p. 39\)](#)
- [Values that You Specify When You Create or Edit Cross-site Scripting Match Conditions \(p. 39\)](#)
- [Adding and Deleting Filters in a Cross-site Scripting Match Condition \(p. 41\)](#)
- [Deleting Cross-site Scripting Match Conditions \(p. 41\)](#)

## Creating Cross-site Scripting Match Conditions

When you create cross-site scripting match conditions, you specify filters, which indicate the part of web requests that you want AWS WAF to inspect for malicious scripts, such as the URI or the query string. You can add more than one filter to a cross-site scripting match condition, or you can create a separate condition for each filter. Here's how each configuration affects AWS WAF behavior:

- **More than one filter per cross-site scripting match condition (recommended)** – When you add a cross-site scripting match condition containing multiple filters to a rule and add the rule to a web ACL, a web request needs only to match one of the filters in the cross-site scripting match condition for AWS WAF to allow or block the request based on that condition.

For example, suppose you create one cross-site scripting match condition, and the condition contains two filters. One filter instructs AWS WAF to inspect the URI for malicious scripts, and the other instructs AWS WAF to inspect the query string. AWS WAF allows or blocks requests if they appear to contain malicious scripts *either* in the URI *or* in the query string.

- **One filter per cross-site scripting match condition** – When you add the separate cross-site scripting match conditions to a rule and add the rule to a web ACL, web requests must match all of the conditions for AWS WAF to allow or block requests based on the conditions.

Suppose you create two conditions, and each condition contains the one of the two filters in the preceding example. When you add both conditions to the same rule and add the rule to a web ACL, AWS WAF allows or blocks requests only when both the URI and the query string appear to contain malicious scripts.

### Note

When you add a cross-site scripting match condition to a rule, you can also configure AWS WAF to allow or block web requests that *do not* appear to contain malicious scripts.

### To create a cross-site scripting match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Cross-site scripting**.
3. Choose **Create condition**.
4. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit Cross-site Scripting Match Conditions \(p. 39\)](#).
5. Choose **Add another filter**.
6. If you want to add another filter, repeat steps 4 and 5.
7. When you're finished adding filters, choose **Create**.

## Values that You Specify When You Create or Edit Cross-site Scripting Match Conditions

When you create or update a cross-site scripting match condition, you specify the following values:

### Name

The name of the cross-site scripting match condition.

The name can contain only the characters A-Z, a-z, and 0-9. You can't change the name of a condition after you create it.

### Part of the request to filter on

Choose the part of each web request that you want AWS WAF to inspect for malicious scripts:

**Header**

A specified request header, for example, the `User-Agent` or `Referer` header. If you choose **Header**, specify the name of the header in the **Header** field.

**HTTP method**

The HTTP method, which indicates the type of operation that the request is asking the origin to perform. CloudFront supports the following methods: `DELETE`, `GET`, `HEAD`, `OPTIONS`, `PATCH`, `POST`, and `PUT`.

**Query string**

The part of a URL that appears after a `?` character, if any.

**URI**

The part of a URL that identifies a resource, for example, `/images/daily-ad.jpg`.

**Body**

The part of a request that contains any additional data that you want to send to your web server as the HTTP request body, such as data from a form.

**Note**

If you choose **Body** for the value of **Part of the request to filter on**, AWS WAF inspects only the first 8192 bytes (8 KB) because CloudFront forwards only the first 8192 bytes for inspection. To allow or block requests for which the body is longer than 8192 bytes, you can create a size constraint condition. (AWS WAF gets the length of the body from the request headers.) For more information, see [Working with Size Constraint Conditions](#) (p. 44).

**Header**

If you chose **Header** for **Part of the request to filter on**, choose a header from the list of common headers, or type the name of a header that you want AWS WAF to inspect for malicious scripts.

**Transformation**

A transformation reformats a web request before AWS WAF inspects the request. This eliminates some of the unusual formatting that attackers use in web requests in an effort to bypass AWS WAF. Transformations can perform the following operations:

**None**

AWS WAF doesn't perform any text transformations on the web request before inspecting it for the string in **Value to match**.

**Convert to lowercase**

AWS WAF converts uppercase letters (A-Z) to lowercase (a-z).

**HTML decode**

AWS WAF replaces HTML-encoded characters with unencoded characters:

- Replaces `&quot;` with `&`
- Replaces `&nbsp;` with a non-breaking space
- Replaces `&lt;` with `<`
- Replaces `&gt;` with `>`
- Replaces characters that are represented in hexadecimal format, `&#xhhhh;`, with the corresponding characters
- Replaces characters that are represented in decimal format, `&#nnnn;`, with the corresponding characters

**Normalize whitespace**

AWS WAF replaces the following characters with a space character (decimal 32):

- `\f`, formfeed, decimal 12
- `\t`, tab, decimal 9
- `\n`, newline, decimal 10
- `\r`, carriage return, decimal 13
- `\v`, vertical tab, decimal 11
- non-breaking space, decimal 160

In addition, this option replaces multiple spaces with one space.

**Simplify command line**

For requests that contain operating system command line commands, use this option to perform the following transformations:

- Delete the following characters: \ " ' ^
- Delete spaces before the following characters: / (
- Replace the following characters with a space: , ;
- Replace multiple spaces with one space
- Convert uppercase letters (A-Z) to lowercase (a-z)

**URL decode**

Decode a URL-encoded request.

## Adding and Deleting Filters in a Cross-site Scripting Match Condition

You can add or delete filters in a cross-site scripting match condition. To change a filter, add a new one and delete the old one.

### To add or delete filters in a cross-site scripting match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Cross-site scripting**.
3. Choose the condition that you want to add or delete filters in.
4. To add filters, perform the following steps:
  - a. Choose **Add filter**.
  - b. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit Cross-site Scripting Match Conditions \(p. 39\)](#).
  - c. Choose **Add**.
5. To delete filters, perform the following steps:
  - a. Select the filter that you want to delete.
  - b. Choose **Delete filter**.

## Deleting Cross-site Scripting Match Conditions

If you want to delete a cross-site scripting match condition, you need to first delete all filters in the condition and remove the condition from all of the rules that are using it, as described in the following procedure.

### To delete a cross-site scripting match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Cross-site scripting**.
3. In the **Cross-site scripting match conditions** pane, choose the cross-site scripting match condition that you want to delete.

4. In the right pane, choose the **Associated rules** tab.

If the list of rules using this cross-site scripting match condition is empty, go to step 6. If the list contains any rules, make note of the rules, and continue with step 5.

5. To remove the cross-site scripting match condition from the rules that are using it, perform the following steps:
  - a. In the navigation pane, choose **Rules**.
  - b. Choose the name of a rule that is using the cross-site scripting match condition that you want to delete.
  - c. In the right pane, select the cross-site scripting match condition that you want to remove from the rule, and choose **Remove selected condition**.
  - d. Repeat steps b and c for all of the remaining rules that are using the cross-site scripting match condition that you want to delete.
  - e. In the navigation pane, choose **Cross-site scripting**.
  - f. In the **Cross-site scripting match conditions** pane, choose the cross-site scripting match condition that you want to delete.
6. Choose **Delete** to delete the selected condition.

## Working with IP Match Conditions

If you want to allow or block web requests based on the IP addresses that the requests originate from, create one or more IP match conditions. An IP match condition lists up to 1000 IP addresses or IP address ranges that your requests originate from. Later in the process, when you create a web ACL, you specify whether to allow or block requests from those IP addresses.

### Topics

- [Creating an IP Match Condition \(p. 42\)](#)
- [Editing IP Match Conditions \(p. 43\)](#)
- [Deleting IP Match Conditions \(p. 44\)](#)

## Creating an IP Match Condition

If you want to allow some web requests and block others based on the IP addresses that the requests originate from, create an IP match condition for the IP addresses that you want to allow and another IP match condition for the IP addresses that you want to block.

### Note

When you add an IP match condition to a rule, you can also configure AWS WAF to allow or block web requests that *do not* originate from the IP addresses that you specify in the condition.

### To create an IP match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **IP addresses**.
3. Choose **Create condition**.
4. Type a name in the **Name** field.

The name can contain only the characters A-Z, a-z, and 0-9. You can't change the name of a condition after you create it.

5. Specify an IP address or range of IP addresses by using CIDR notation. Here are two examples:
  - To specify the IP address 192.0.2.44, type **192.0.2.44/32**.
  - To specify the range of IP addresses from 192.0.2.0 to 192.0.2.255, type **192.0.2.0/24**.

AWS WAF supports /8, /16, /24, and /32 IP address ranges. For more information about CIDR notation, see the Wikipedia entry [Classless Inter-Domain Routing](#).

**Note**

AWS WAF currently supports only IPv4 IP addresses.

6. Choose **Add another IP address or range**.
7. If you want to add another IP address or range, repeat steps 5 and 6.
8. When you're finished adding values, choose **Create IP match condition**.

## Editing IP Match Conditions

You can add an IP address range to an IP match condition or delete a range. To change a range, add a new one and delete the old one.

### To edit an IP match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **IP addresses**.
3. In the **IP match conditions** pane, choose the IP match condition that you want to edit.
4. To add an IP address range:
  - a. In the right pane, choose **Add IP address or range**.
  - b. Type an IP address range by using CIDR notation. Here are two examples:
    - To specify the IP address 192.0.2.44, type **192.0.2.44/32**.
    - To specify the range of IP addresses from 192.0.2.0 to 192.0.2.255, type **192.0.2.0/24**.

AWS WAF supports /8, /16, /24, and /32 IP address ranges. For more information about CIDR notation, see the Wikipedia entry [Classless Inter-Domain Routing](#).

**Note**

AWS WAF currently supports only IPv4 IP addresses.

- c. To add more IP addresses, choose **Add another IP address** and type the value.
  - d. Choose **Add**.
5. To delete an IP address or range:
  - a. In the right pane, select the values that you want to delete.
  - b. Choose **Delete IP address or range**.



## Deleting IP Match Conditions

If you want to delete an IP match condition, you need to first delete all IP addresses and ranges in the condition and remove the condition from all of the rules that are using it, as described in the following procedure.

### To delete an IP match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **IP addresses**.
3. In the **IP match conditions** pane, choose the IP match condition that you want to delete.
4. In the right pane, choose the **Rules** tab.

If the list of rules using this IP match condition is empty, go to step 6. If the list contains any rules, make note of the rules, and continue with step 5.

5. To remove the IP match condition from the rules that are using it, perform the following steps:
  - a. In the navigation pane, choose **Rules**.
  - b. Choose the name of a rule that is using the IP match condition that you want to delete.
  - c. In the right pane, select the IP match condition that you want to remove from the rule, and choose **Remove selected condition**.
  - d. Repeat steps b and c for all of the remaining rules that are using the IP match condition that you want to delete.
  - e. In the navigation pane, choose **IP match conditions**.
  - f. In the **IP match conditions** pane, choose the IP match condition that you want to delete.
6. Choose **Delete** to delete the selected condition.

## Working with Size Constraint Conditions

If you want to allow or block web requests based on the length of specified parts of requests, create one or more size constraint conditions. A size constraint condition identifies the part of web requests that you want AWS WAF to look at, the number of bytes that you want AWS WAF to look for, and an operator, such as greater than or less than. For example, you can use a size constraint condition to look for query strings that are longer than 100 bytes. Later in the process, when you create a web ACL, you specify whether to allow or block requests based on those settings.

Note that if you configure AWS WAF to inspect the request body, for example, by searching the body for a specified string, AWS WAF inspects only the first 8192 bytes (8 KB). If the request body for your web requests will never exceed 8192 bytes, you can create a size constraint condition and block requests that have a request body greater than 8192 bytes.

### Topics

- [Creating Size Constraint Conditions \(p. 45\)](#)
- [Values that You Specify When You Create or Edit Size Constraint Conditions \(p. 45\)](#)
- [Adding and Deleting Filters in a Size Constraint Condition \(p. 47\)](#)
- [Deleting Size Constraint Conditions \(p. 48\)](#)

## Creating Size Constraint Conditions

When you create size constraint conditions, you specify filters that identify the part of web requests for which you want AWS WAF to evaluate the length. You can add more than one filter to a size constraint condition, or you can create a separate condition for each filter. Here's how each configuration affects AWS WAF behavior:

- **One filter per size constraint condition** – When you add the separate size constraint conditions to a rule and add the rule to a web ACL, web requests must match all of the conditions for AWS WAF to allow or block requests based on the conditions.

For example, suppose you create two conditions. One matches web requests for which query strings are greater than 100 bytes. The other matches web requests for which the request body is greater than 1024 bytes. When you add both conditions to the same rule and add the rule to a web ACL, AWS WAF allows or blocks requests only when both conditions are true.

- **More than one filter per size constraint condition** – When you add a size constraint condition containing multiple filters to a rule and add the rule to a web ACL, a web request needs only to match one of the filters in the size constraint condition for AWS WAF to allow or block the request based on that condition.

Suppose you create one condition instead of two, and the one condition contains the same two filters as in the preceding example. AWS WAF allows or blocks requests if either the query string is greater than 100 bytes or the request body is greater than 1024 bytes.

### Note

When you add a size constraint condition to a rule, you can also configure AWS WAF to allow or block web requests that *do not* match the values in the condition.

### To create a size constraint condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Size constraints**.
3. Choose **Create condition**.
4. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit Size Constraint Conditions \(p. 45\)](#).
5. Choose **Add another filter**.
6. If you want to add another filter, repeat steps 4 and 5.
7. When you're finished adding filters, choose **Create size constraint condition**.

## Values that You Specify When You Create or Edit Size Constraint Conditions

When you create or update a size constraint condition, you specify the following values:

### Name

Type a name for the size constraint condition.

The name can contain only the characters A-Z, a-z, and 0-9. You can't change the name of a condition after you create it.

### Part of the request to filter on

Choose the part of each web request for which you want AWS WAF to evaluate the length:

**AWS WAF Developer Guide**  
**Values that You Specify When You Create or Edit Size**  
**Constraint Conditions**

---

**Header**

A specified request header, for example, the `User-Agent` or `Referer` header. If you choose **Header**, specify the name of the header in the **Header** field.

**HTTP method**

The HTTP method, which indicates the type of operation that the request is asking the origin to perform. CloudFront supports the following methods: `DELETE`, `GET`, `HEAD`, `OPTIONS`, `PATCH`, `POST`, and `PUT`.

**Query string**

The part of a URL that appears after a `?` character, if any.

**URI**

The part of a URL that identifies a resource, for example, `/images/daily-ad.jpg`.

**Body**

The part of a request that contains any additional data that you want to send to your web server as the HTTP request body, such as data from a form.

**Header (Only When "Part of the request to filter on" is "Header")**

If you chose **Header** for **Part of the request to filter on**, choose a header from the list of common headers, or type the name of a header for which you want AWS WAF to evaluate the length.

**Comparison operator**

Choose how you want AWS WAF to evaluate the length of the query string in web requests with respect to the value that you specify for **Size**.

For example, if you choose **Is greater than** for **Comparison operator** and type **100** for **Size**, AWS WAF evaluates web requests for a query string that is longer than 100 bytes.

**Size**

Type the length, in bytes, that you want AWS WAF to watch for in query strings.

**Note**

If you choose **URI** for the value of **Part of the request to filter on**, the `/` in the URI counts as one character. For example, the URI `/logo.jpg` is nine characters long.

**Transformation**

A transformation reformats a web request before AWS WAF evaluates the length of the specified part of the request. This eliminates some of the unusual formatting that attackers use in web requests in an effort to bypass AWS WAF. Transformations can perform the following operations:

**Note**

If you choose **Body** for **Part of the request to filter on**, you can't configure AWS WAF to perform a transformation because CloudFront forwards only the first 8192 bytes for inspection. However, you can still filter your traffic based on the size of the HTTP request body and specify a transformation of `None`. (AWS WAF gets the length of the body from the request headers.)

**None**

AWS WAF doesn't perform any text transformations on the web request before checking the length.

**Convert to lowercase**

AWS WAF converts uppercase letters (A-Z) to lowercase (a-z).

**HTML decode**

AWS WAF replaces HTML-encoded characters with unencoded characters:

- Replaces `&quot;` with `&`
- Replaces `&nbsp;` with a non-breaking space
- Replaces `&lt;` with `<`
- Replaces `&gt;` with `>`
- Replaces characters that are represented in hexadecimal format, `&#xhhhh;`, with the corresponding characters

- Replaces characters that are represented in decimal format, `&#nnnn;`, with the corresponding characters

**Normalize whitespace**

AWS WAF replaces the following characters with a space character (decimal 32):

- `\f`, formfeed, decimal 12
- `\t`, tab, decimal 9
- `\n`, newline, decimal 10
- `\r`, carriage return, decimal 13
- `\v`, vertical tab, decimal 11
- non-breaking space, decimal 160

In addition, this option replaces multiple spaces with one space.

**Simplify command line**

For requests that contain operating system command line commands, use this option to perform the following transformations:

- Delete the following characters: `\ " ' ^`
- Delete spaces before the following characters: `/ (`
- Replace the following characters with a space: `, ;`
- Replace multiple spaces with one space
- Convert uppercase letters (A-Z) to lowercase (a-z)

**URL decode**

Decode a URL-encoded request.

## Adding and Deleting Filters in a Size Constraint Condition

You can add or delete filters in a size constraint condition. To change a filter, add a new one and delete the old one.

**To add or delete filters in a size constraint condition**

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Size constraint**.
3. Choose the condition that you want to add or delete filters in.
4. To add filters, perform the following steps:
  - a. Choose **Add filter**.
  - b. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit Size Constraint Conditions](#) (p. 45).
  - c. Choose **Add**.
5. To delete filters, perform the following steps:
  - a. Select the filter that you want to delete.
  - b. Choose **Delete filter**.

## Deleting Size Constraint Conditions

If you want to delete a size constraint condition, you need to first delete all filters in the condition and remove the condition from all of the rules that are using it, as described in the following procedure.

### To delete a size constraint condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Size constraints**.
3. In the **Size constraint conditions** pane, choose the size constraint condition that you want to delete.
4. In the right pane, choose the **Associated rules** tab.

If the list of rules using this size constraint condition is empty, go to step 6. If the list contains any rules, make note of the rules, and continue with step 5.

5. To remove the size constraint condition from the rules that are using it, perform the following steps:
  - a. In the navigation pane, choose **Rules**.
  - b. Choose the name of a rule that is using the size constraint condition that you want to delete.
  - c. In the right pane, select the size constraint condition that you want to remove from the rule, and choose **Remove selected condition**.
  - d. Repeat steps b and c for all of the remaining rules that are using the size constraint condition that you want to delete.
  - e. In the navigation pane, choose **Size constraint**.
  - f. In the **Size constraint conditions** pane, choose the size constraint condition that you want to delete.
6. Choose **Delete** to delete the selected condition.

## Working with SQL Injection Match Conditions

Attackers sometimes insert malicious SQL code into web requests in an effort to extract data from your database. To allow or block web requests that appear to contain malicious SQL code, create one or more SQL injection match conditions. A SQL injection match condition identifies the part of web requests, such as the URI or the query string, that you want AWS WAF to inspect. Later in the process, when you create a web ACL, you specify whether to allow or block requests that appear to contain malicious SQL code.

### Topics

- [Creating SQL Injection Match Conditions \(p. 48\)](#)
- [Values that You Specify When You Create or Edit SQL Injection Match Conditions \(p. 49\)](#)
- [Adding and Deleting Filters in a SQL Injection Match Condition \(p. 51\)](#)
- [Deleting SQL Injection Match Conditions \(p. 51\)](#)

## Creating SQL Injection Match Conditions

When you create SQL injection match conditions, you specify filters, which indicate the part of web requests that you want AWS WAF to inspect for malicious SQL code, such as the URI or the query string. You can add more than one filter to a SQL injection match condition, or you can create a separate condition for each filter. Here's how each configuration affects AWS WAF behavior:

- **More than one filter per SQL injection match condition (recommended)** – When you add a SQL injection match condition containing multiple filters to a rule and add the rule to a web ACL, a web request needs only to match one of the filters in the SQL injection match condition for AWS WAF to allow or block the request based on that condition.

For example, suppose you create one SQL injection match condition, and the condition contains two filters. One filter instructs AWS WAF to inspect the URI for malicious SQL code, and the other instructs AWS WAF to inspect the query string. AWS WAF allows or blocks requests if they appear to contain malicious SQL code *either* in the URI *or* in the query string.

- **One filter per SQL injection match condition** – When you add the separate SQL injection match conditions to a rule and add the rule to a web ACL, web requests must match all of the conditions for AWS WAF to allow or block requests based on the conditions.

Suppose you create two conditions, and each condition contains the one of the two filters in the preceding example. When you add both conditions to the same rule and add the rule to a web ACL, AWS WAF allows or blocks requests only when both the URI and the query string appear to contain malicious SQL code.

#### **Note**

When you add a SQL injection match condition to a rule, you can also configure AWS WAF to allow or block web requests that *do not* appear to contain malicious SQL code.

#### **To create a SQL injection match condition**

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **SQL injection**.
3. Choose **Create condition**.
4. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit SQL Injection Match Conditions \(p. 49\)](#).
5. Choose **Add another filter**.
6. If you want to add another filter, repeat steps 4 and 5.
7. When you're finished adding filters, choose **Create**.

## **Values that You Specify When You Create or Edit SQL Injection Match Conditions**

When you create or update a SQL injection match condition, you specify the following values:

#### **Name**

The name of the SQL injection match condition.

The name can contain only the characters A-Z, a-z, and 0-9. You can't change the name of a condition after you create it.

#### **Part of the request to filter on**

Choose the part of each web request that you want AWS WAF to inspect for malicious SQL code:

##### **Header**

A specified request header, for example, the `User-Agent` or `Referer` header. If you choose **Header**, specify the name of the header in the **Header** field.

##### **HTTP method**

The HTTP method, which indicates the type of operation that the request is asking the origin to perform. CloudFront supports the following methods: `DELETE`, `GET`, `HEAD`, `OPTIONS`, `PATCH`, `POST`, and `PUT`.

**Query string**

The part of a URL that appears after a ? character, if any.

**URI**

The part of a URL that identifies a resource, for example, `/images/daily-ad.jpg`.

**Body**

The part of a request that contains any additional data that you want to send to your web server as the HTTP request body, such as data from a form.

**Note**

If you choose **Body** for the value of **Part of the request to filter on**, AWS WAF inspects only the first 8192 bytes (8 KB) because CloudFront forwards only the first 8192 bytes for inspection. To allow or block requests for which the body is longer than 8192 bytes, you can create a size constraint condition. (AWS WAF gets the length of the body from the request headers.) For more information, see [Working with Size Constraint Conditions](#) (p. 44).

**Header**

If you chose **Header** for **Part of the request to filter on**, choose a header from the list of common headers, or type the name of a header that you want AWS WAF to inspect for malicious SQL code.

**Transformation**

A transformation reformats a web request before AWS WAF inspects the request. This eliminates some of the unusual formatting that attackers use in web requests in an effort to bypass AWS WAF. Transformations can perform the following operations:

**None**

AWS WAF doesn't perform any text transformations on the web request before inspecting it for the string in **Value to match**.

**Convert to lowercase**

AWS WAF converts uppercase letters (A-Z) to lowercase (a-z).

**HTML decode**

AWS WAF replaces HTML-encoded characters with unencoded characters:

- Replaces `&quot;` with `&`
- Replaces `&nbsp;` with a non-breaking space
- Replaces `&lt;` with `<`
- Replaces `&gt;` with `>`
- Replaces characters that are represented in hexadecimal format, `&#xhhhh;`, with the corresponding characters
- Replaces characters that are represented in decimal format, `&#nnnn;`, with the corresponding characters

**Normalize whitespace**

AWS WAF replaces the following characters with a space character (decimal 32):

- `\f`, formfeed, decimal 12
- `\t`, tab, decimal 9
- `\n`, newline, decimal 10
- `\r`, carriage return, decimal 13
- `\v`, vertical tab, decimal 11
- non-breaking space, decimal 160

In addition, this option replaces multiple spaces with one space.

**Simplify command line**

For requests that contain operating system command line commands, use this option to perform the following transformations:

- Delete the following characters: `\ " ' ^`
- Delete spaces before the following characters: `/ (`

- Replace the following characters with a space: , ;
- Replace multiple spaces with one space
- Convert uppercase letters (A-Z) to lowercase (a-z)

**URL decode**

Decode a URL-encoded request.

## Adding and Deleting Filters in a SQL Injection Match Condition

You can add or delete filters in a SQL injection match condition. To change a filter, add a new one and delete the old one.

### To add or delete filters in a SQL injection match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **SQL injection**.
3. Choose the condition that you want to add or delete filters in.
4. To add filters, perform the following steps:
  - a. Choose **Add filter**.
  - b. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit SQL Injection Match Conditions \(p. 49\)](#).
  - c. Choose **Add**.
5. To delete filters, perform the following steps:
  - a. Select the filter that you want to delete.
  - b. Choose **Delete filter**.

## Deleting SQL Injection Match Conditions

If you want to delete a SQL injection match condition, you need to first delete all filters in the condition and remove the condition from all of the rules that are using it, as described in the following procedure.

### To delete a SQL injection match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **SQL injection**.
3. In the **SQL injection match conditions** pane, choose the SQL injection match condition that you want to delete.
4. In the right pane, choose the **Associated rules** tab.

If the list of rules using this SQL injection match condition is empty, go to step 6. If the list contains any rules, make note of the rules, and continue with step 5.
5. To remove the SQL injection match condition from the rules that are using it, perform the following steps:



- a. In the navigation pane, choose **Rules**.
  - b. Choose the name of a rule that is using the SQL injection match condition that you want to delete.
  - c. In the right pane, select the SQL injection match condition that you want to remove from the rule, and choose **Remove selected condition**.
  - d. Repeat steps b and c for all of the remaining rules that are using the SQL injection match condition that you want to delete.
  - e. In the navigation pane, choose **SQL injection**.
  - f. In the **SQL injection match conditions** pane, choose the SQL injection match condition that you want to delete.
6. Choose **Delete** to delete the selected condition.

## Working with String Match Conditions

If you want to allow or block web requests based on strings that appear in the requests, create one or more string match conditions. A string match condition identifies the string that you want to search for and the part of web requests, such as a specified header or the query string, that you want AWS WAF to inspect for the string. Later in the process, when you create a web ACL, you specify whether to allow or block requests that contain the string.

### Topics

- [Creating a String Match Condition \(p. 52\)](#)
- [Values that You Specify When You Create or Edit String Match Conditions \(p. 53\)](#)
- [Adding and Deleting Filters in a String Match Condition \(p. 55\)](#)
- [Deleting String Match Conditions \(p. 55\)](#)

## Creating a String Match Condition

When you create string match conditions, you specify filters that identify the string that you want to search for and the part of web requests that you want AWS WAF to inspect for that string, such as the URI or the query string. You can add more than one filter to a string match condition, or you can create a separate string match condition for each filter. Here's how each configuration affects AWS WAF behavior:

- **One filter per string match condition** – When you add the separate string match conditions to a rule and add the rule to a web ACL, web requests must match all of the conditions for AWS WAF to allow or block requests based on the conditions.

For example, suppose you create two conditions. One matches web requests that contain the value `BadBot` in the `User-Agent` header. The other matches web requests that contain the value `BadParameter` in query strings. When you add both conditions to the same rule and add the rule to a web ACL, AWS WAF allows or blocks requests only when they contain both values.

- **More than one filter per string match condition** – When you add a string match condition containing multiple filters to a rule and add the rule to a web ACL, a web request needs only to match one of the filters in the string match condition for AWS WAF to allow or block the request based on the one condition.

Suppose you create one condition instead of two, and the one condition contains the same two filters as in the preceding example. AWS WAF allows or blocks requests if they contain *either* `BadBot` in the `User-Agent` header *or* `BadParameter` in the query string.

**Note**

When you add a string match condition to a rule, you can also configure AWS WAF to allow or block web requests that *do not* match the values in the condition.

**To create a string match condition**

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **String matching**.
3. Choose **Create condition**.
4. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit String Match Conditions \(p. 53\)](#).
5. Choose **Add another filter**.
6. If you want to add another filter, repeat steps 4 and 5.
7. When you're finished adding filters, choose **Create string match condition**.

## Values that You Specify When You Create or Edit String Match Conditions

When you create or update a string match condition, you specify the following values:

**Name**

Type a name for the string match condition. The value can contain only the characters A-Z, a-z, and 0-9. You can't change the name of a condition after you create it.

**Part of the request to filter on**

Choose the part of each web request that you want AWS WAF to inspect for the string that you specify in **Value to match**:

**Header**

A specified request header, for example, the `User-Agent` or `Referer` header. If you choose **Header**, specify the name of the header in the **Header** field.

**HTTP method**

The HTTP method, which indicates the type of operation that the request is asking the origin to perform. CloudFront supports the following methods: `DELETE`, `GET`, `HEAD`, `OPTIONS`, `PATCH`, `POST`, and `PUT`.

**Query string**

The part of a URL that appears after a `?` character, if any.

**URI**

The part of a URL that identifies a resource, for example, `/images/daily-ad.jpg`.

**Body**

The part of a request that contains any additional data that you want to send to your web server as the HTTP request body, such as data from a form.

**Note**

If you choose **Body** for the value of **Part of the request to filter on**, AWS WAF inspects only the first 8192 bytes (8 KB) because CloudFront forwards only the first 8192 bytes for inspection. To allow or block requests for which the body is longer than 8192 bytes, you can create a size constraint condition. (AWS WAF gets the length of the body from the request headers.) For more information, see [Working with Size Constraint Conditions \(p. 44\)](#).

**Header (Only When "Part of the request to filter on" is "Header")**

If you chose **Header** from the **Part of the request to filter on** list, choose a header from the list of common headers, or type the name of a header that you want AWS WAF to inspect.

### **Match type**

Within the part of the request that you want AWS WAF to inspect, choose where the string in **Value to match** must appear to match this filter:

#### **Contains**

The string appears anywhere in the specified part of the request.

#### **Contains word**

The specified part of the web request must include **Value to match**, and **Value to match** must contain only alphanumeric characters or underscore (A-Z, a-z, 0-9, or `_`). In addition, **Value to match** must be a word, which means one of the following:

- **Value to match** exactly matches the value of the specified part of the web request, such as the value of a header.
- **Value to match** is at the beginning of the specified part of the web request and is followed by a character other than an alphanumeric character or underscore (`_`), for example, `BadBot;`.
- **Value to match** is at the end of the specified part of the web request and is preceded by a character other than an alphanumeric character or underscore (`_`), for example, `;BadBot`.
- **Value to match** is in the middle of the specified part of the web request and is preceded and followed by characters other than alphanumeric characters or underscore (`_`), for example, `-BadBot;`.

#### **Exactly matches**

The string and the value of the specified part of the request are identical.

#### **Starts with**

The string appears at the beginning of the specified part of the request.

#### **Ends with**

The string appears at the end of the specified part of the request.

### **Transformation**

A transformation reformats a web request before AWS WAF inspects the request. This eliminates some of the unusual formatting that attackers use in web requests in an effort to bypass AWS WAF. Transformations can perform the following operations:

#### **None**

AWS WAF doesn't perform any text transformations on the web request before inspecting it for the string in **Value to match**.

#### **Convert to lowercase**

AWS WAF converts uppercase letters (A-Z) to lowercase (a-z).

#### **HTML decode**

AWS WAF replaces HTML-encoded characters with unencoded characters:

- Replaces `&quot;` with `&`
- Replaces `&nbsp;` with a non-breaking space
- Replaces `&lt;` with `<`
- Replaces `&gt;` with `>`
- Replaces characters that are represented in hexadecimal format, `&#xhhhh;`, with the corresponding characters
- Replaces characters that are represented in decimal format, `&#nnnn;`, with the corresponding characters

#### **Normalize whitespace**

AWS WAF replaces the following characters with a space character (decimal 32):

- `\f`, formfeed, decimal 12
- `\t`, tab, decimal 9
- `\n`, newline, decimal 10
- `\r`, carriage return, decimal 13
- `\v`, vertical tab, decimal 11
- non-breaking space, decimal 160

In addition, this option replaces multiple spaces with one space.

**Simplify command line**

When you're concerned that attackers are injecting an operating system commandline command and using unusual formatting to disguise some or all of the command, use this option to perform the following transformations:

- Delete the following characters: \ " ' ^
- Delete spaces before the following characters: / (
- Replace the following characters with a space: , ;
- Replace multiple spaces with one space
- Convert uppercase letters (A-Z) to lowercase (a-z)

**URL decode**

Decode a URL-encoded request.

**Value is base64 encoded**

If the value in **Value to match** is base64-encoded, select this check box. Use base64-encoding to specify non-printable characters, such as tabs and linefeeds, that attackers include in their requests.

**Value to match**

Specify the value that you want AWS WAF to search for in web requests. The maximum length is 50 bytes. If you're base64-encoding the value, the 50-byte limit applies to the value before you encode it.

## Adding and Deleting Filters in a String Match Condition

You can add filters to a string match condition or delete filters. To change a filter, add a new one and delete the old one.

**To add or delete filters in a string match condition**

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **String matching**.
3. Choose the condition that you want to add or delete filters in.
4. To add filters, perform the following steps:
  - a. Choose **Add filter**.
  - b. Specify the applicable filter settings. For more information, see [Values that You Specify When You Create or Edit String Match Conditions \(p. 53\)](#).
  - c. Choose **Add**.
5. To delete filters, perform the following steps:
  - a. Select the filter that you want to delete.
  - b. Choose **Delete Filter**.

## Deleting String Match Conditions

If you want to delete a string match condition, you need to first delete all filters in the condition and remove the condition from all of the rules that are using it, as described in the following procedure.

### To delete a string match condition

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **String matching**.
3. In the **String match conditions** pane, choose the string match condition that you want to delete.
4. In the right pane, choose the **Rules** tab.

If the list of rules using this string match condition is empty, go to step 6. If the list contains any rules, make note of the rules, and continue with step 5.

5. To remove the string match condition from the rules that are using it, perform the following steps:
  - a. In the navigation pane, choose **Rules**.
  - b. Choose the name of a rule that is using the string match condition that you want to delete.
  - c. In the right pane, select the string match condition that you want to remove from the rule, and choose **Remove selected condition**.
  - d. Repeat steps b and c for all of the remaining rules that are using the string match condition that you want to delete.
  - e. In the navigation pane, choose **String match**.
  - f. In the **String match conditions** pane, choose the string match condition that you want to delete.
6. Choose **Delete** to delete the selected condition.

## Working with Rules

Rules let you precisely target the web requests that you want AWS WAF to allow or block by specifying the exact conditions that you want AWS WAF to watch for, such as the IP addresses that requests originate from, the strings that the requests contain and where the strings appear, and whether the requests appear to contain malicious SQL code.

### Topics

- [Creating a Rule and Adding Conditions \(p. 56\)](#)
- [Adding and Removing Conditions in a Rule \(p. 57\)](#)
- [Deleting a Rule \(p. 58\)](#)
- [Listing the Web ACLs that Include a Specified Rule \(p. 59\)](#)

## Creating a Rule and Adding Conditions

If you add more than one condition to a rule, a web request must match all of the conditions for AWS WAF to allow or block requests based on that rule.

### To create a rule and add conditions

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Rules**.
3. Choose **Create rule**.
4. Type the following values:

**Name**

Type a name.

**CloudWatch metric name**

Type a name for the CloudWatch metric that AWS WAF will create and will associate with the rule. The name can contain only alphanumeric characters (A-Z, a-z, 0-9); it can't contain whitespace.

**Note**

You can't change the metric name after you create the rule.

5. To add a condition to the rule, specify the following values:

**When a request does/does not**

If you want AWS WAF to allow or block requests based on the filters in a condition, for example, web requests that originate from the range of IP addresses 192.0.2.0/24, choose **does**.

If you want AWS WAF to allow or block requests based on the inverse of the filters in a condition, choose **does not**. For example, if an IP match condition includes the IP address range 192.0.2.0/24 and you want AWS WAF to allow or block requests that *do not* come from those IP addresses, choose **does not**.

**match/originate from**

Choose the type of condition that you want to add to the rule:

- Cross-site scripting match conditions – choose **match at least one of the filters in the cross-site scripting match condition**
- IP match conditions – choose **originate from an IP address in**
- Size constraint conditions – choose **match at least one of the filters in the size constraint condition**
- SQL injection match conditions – choose **match at least one of the filters in the SQL injection match condition**
- String match conditions – choose **match at least one of the filters in the string match condition**

**condition name**

Choose the condition that you want to add to the rule. The list displays only conditions of the type that you chose in the preceding step.

6. To add another condition to the rule, choose **Add another condition**, and repeat steps 4 and 5. Note the following:
  - If you add more than one condition, a web request must match at least one filter in every condition for AWS WAF to allow or block requests based on that rule
  - If you add two IP match conditions to the same rule, AWS WAF will only allow or block requests that originate from IP addresses that appear in both IP match conditions
7. When you're finished adding conditions, choose **Create**.

## Adding and Removing Conditions in a Rule

You can change a rule by adding or removing conditions.

### To add or remove conditions in a rule

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Rules**.
3. Choose the rule in which you want to add or remove conditions.
4. To add a condition, choose **Add condition** and specify the following values:

#### When a request does/does not

If you want AWS WAF to allow or block requests based on the filters in a condition, for example, web requests that originate from the range of IP addresses 192.0.2.0/24, choose **does**.

If you want AWS WAF to allow or block requests based on the inverse of the filters in a condition, choose **does not**. For example, if an IP match condition includes the IP address range 192.0.2.0/24 and you want AWS WAF to allow or block requests that *do not* come from those IP addresses, choose **does not**.

#### match/originate from

Choose the type of condition that you want to add to the rule:

- Cross-site scripting match conditions – choose **match at least one of the filters in the cross-site scripting match condition**
- IP match conditions – choose **originate from an IP address in**
- Size constraint conditions – choose **match at least one of the filters in the size constraint condition**
- SQL injection match conditions – choose **match at least one of the filters in the SQL injection match condition**
- String match conditions – choose **match at least one of the filters in the string match condition**

#### condition name

Choose the condition that you want to add to the rule. The list displays only conditions of the type that you chose in the preceding step.

5. To remove a condition, select the condition, and choose **Remove selected condition**.

## Deleting a Rule

If you want to delete a rule, you need to first remove the rule from the web ACLs that are using it and remove the conditions that are included in the rule.

### To delete a rule

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Rules**.
3. In the **Rules** pane, choose the rule that you want to delete.
4. In the right pane, choose the **Web ACLs** tab.

If the list of the web ACLs that are using this rule is empty, go to step 6. If the list contains any web ACLs, make note of them, and continue with step 5.

5. To remove the rule from the web ACLs that are using it, perform the following steps:
  - a. In the navigation pane, choose **Web ACLs**.
  - b. Choose the name of a web ACL that is using the rule that you want to delete.

- c. In the right pane, select the rule that you want to remove from the web ACL, and choose **Remove selected rule**.
  - d. Repeat steps b and c for all of the remaining web ACLs that are using the rule that you want to delete.
  - e. In the navigation pane, choose **Rules**.
  - f. In the **Rules** pane, choose the rule that you want to delete.
6. To delete the selected rule, choose **Actions**, and then choose **Delete**.

## Listing the Web ACLs that Include a Specified Rule

If you want to know which web ACLs will be affected if you edit or delete a rule, perform the following procedure.

### To list the web ACLs that include a rule

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Rules**.
3. In the **Rules** pane, choose the rule for which you want to find the associated web ACLs.
4. In the right pane, choose the **Web ACLs** tab.

## Working with Web ACLs

When you add rules to a web ACL, you specify whether you want AWS WAF to allow or block requests based on the conditions in the rules. If you add more than one rule to a web ACL, AWS WAF evaluates each request against the rules in the order that you list them in the web ACL. When a web request matches all of the conditions in a rule, AWS WAF immediately takes the corresponding action—allow or block—and doesn't evaluate the request against the remaining rules in the web ACL, if any.

If a web request doesn't match any of the rules in a web ACL, AWS WAF takes the default action that you specified for the web ACL. For more information, see [Deciding on the Default Action for a Web ACL](#) (p. 38).

If you want to test a rule before you start using it to allow or block requests, you can configure AWS WAF to count the web requests that match the conditions in the rule. For more information, see [Testing Web ACLs](#) (p. 64).

### Topics

- [Creating a Web ACL](#) (p. 59)
- [Associating or Disassociating a Web ACL with a CloudFront Distribution](#) (p. 62)
- [Editing a Web ACL](#) (p. 62)
- [Deleting a Web ACL](#) (p. 63)

## Creating a Web ACL

### To create a web ACL

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.



2. In the navigation pane, choose **Web ACLs**.
3. Choose **Create web ACL**.
4. Type a name in the **Web ACL name** field. The name that you specify also appears in the CloudFront console in the settings for the distribution that you associate with this web ACL.

**Note**

You can't change the name after you create the web ACL.

5. Change the default name in the **CloudWatch metric name** field if applicable. The name can contain only alphanumeric characters (A-Z, a-z, 0-9); it can't contain whitespace.

**Note**

You can't change the name after you create the web ACL.

6. If you've already created the conditions that you want AWS WAF to use to inspect your web requests, continue with step 7.

If you haven't already created conditions, do so now. For more information, see the following topics:

- [Working with Cross-site Scripting Match Conditions \(p. 38\)](#)
- [Working with IP Match Conditions \(p. 42\)](#)
- [Working with Size Constraint Conditions \(p. 44\)](#)
- [Working with SQL Injection Match Conditions \(p. 48\)](#)
- [Working with String Match Conditions \(p. 52\)](#)

7. Choose **Next**.
8. If you've already created the rules that you want to add to this web ACL, add the rules to the web ACL:
  - a. In the **Rules** list, choose a rule.
  - b. Choose **Add rule to web ACL**.
  - c. Repeat steps a and b until you've added all of the rules that you want to add to this web ACL.
  - d. Go to step 10.
9. If you haven't created rules yet, you can add rules now:
  - a. Choose **Create rule**.
  - b. Type the following values:

**Name**

Type a name.

**CloudWatch metric name**

Type a name for the CloudWatch metric that AWS WAF will create and will associate with the rule. The name can contain only alphanumeric characters (A-Z, a-z, 0-9); it can't contain whitespace.

**Note**

You can't change the metric name after you create the rule.

- c. To add a condition to the rule, specify the following values:

**When a request does/does not**

If you want AWS WAF to allow or block requests based on the filters in a condition, for example, web requests that originate from the range of IP addresses 192.0.2.0/24, choose **does**.

If you want AWS WAF to allow or block requests based on the inverse of the filters in a condition, choose **does not**. For example, if an IP match condition includes the IP address range 192.0.2.0/24 and you want AWS WAF to allow or block requests that *do not* come from those IP addresses, choose **does not**.

**match/originate from**

Choose the type of condition that you want to add to the rule:

- Cross-site scripting match conditions – choose **match at least one of the filters in the cross-site scripting match condition**
- IP match conditions – choose **originate from an IP address in**
- Size constraint conditions – choose **match at least one of the filters in the size constraint condition**
- SQL injection match conditions – choose **match at least one of the filters in the SQL injection match condition**
- String match conditions – choose **match at least one of the filters in the string match condition**

**condition name**

Choose the condition that you want to add to the rule. The list displays only conditions of the type that you chose in the preceding list.

- To add another condition to the rule, choose **Add another condition**, and repeat steps b and c. Note the following:
    - If you add more than one condition, a web request must match at least one filter in every condition for AWS WAF to allow or block requests based on that rule
    - If you add two IP match conditions to the same rule, AWS WAF will only allow or block requests that originate from IP addresses that appear in both IP match conditions
  - Repeat step 9 until you've created all of the rules that you want to add to this web ACL.
  - Choose **Create**.
  - Continue with step 10.
- For each rule that you've added to the web ACL, choose whether you want AWS WAF to allow, block, or count web requests based on the conditions in the rule:
    - **Allow** – CloudFront responds with the requested object or, if the object isn't in the edge cache, forwards the request to the origin.
    - **Block** – CloudFront responds to the request with an HTTP 403 (Forbidden) status code or with a custom error page. For more information, see [Using AWS WAF with CloudFront Custom Error Pages \(p. 71\)](#).
    - **Count** – AWS WAF increments a counter of requests that match the conditions in the rule and then continues to inspect the web request based on the remaining rules in the web ACL.

For information about using **Count** to test a web ACL before you start to use it to allow or block web requests, see [Counting the Web Requests that Match the Rules in a Web ACL \(p. 64\)](#).
  - If you want to change the order of the rules in the web ACL, use the arrows in the **Order** column. AWS WAF inspects web requests based on the order in which rules appear in the web ACL.
  - If you want to remove a rule that you added to the web ACL, choose the **x** in the row for the rule.
  - Choose the default action for the web ACL. This is the action that AWS WAF takes when a web request doesn't match the conditions in any of the rules in this web ACL. For more information, see [Deciding on the Default Action for a Web ACL \(p. 38\)](#).

14. Choose **Next**.
15. On the **Choose AWS resource** page, for **Resource**, choose the CloudFront distribution that you want to associate this web ACL with.
16. Choose **Review and create**.
17. Review the settings for the web ACL, and choose **Confirm and create**.

## Associating or Disassociating a Web ACL with a CloudFront Distribution

To associate or disassociate a CloudFront distribution with a web ACL, perform the applicable procedure. Note that you can also associate a web ACL with a distribution when you create or update the distribution. For more information, see [Using AWS WAF to Control Access to Your Content](#) in the *Amazon CloudFront Developer Guide*.

### Note

You can associate a web ACL with as many CloudFront distributions as you want, but you can associate only one web ACL with a given distribution.

### To associate a web ACL with a CloudFront distribution

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to associate with a CloudFront distribution.
4. On the **Rules** tab, under **AWS resources using this web ACL**, choose **Add association**.
5. When prompted, use the **Resource** list to choose the distribution that you want to associate this web ACL with.
6. Choose **Add**.
7. To associate this web ACL with additional CloudFront distributions, repeat steps 4 through 6.

### To disassociate a web ACL from a CloudFront distribution

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to disassociate from a CloudFront distribution.
4. On the **Rules** tab, under **AWS resources using this web ACL**, choose the x for each CloudFront distribution that you want to disassociate this web ACL from.

## Editing a Web ACL

To add or remove rules from a web ACL or change the default action, perform the following procedure.

### To edit a web ACL

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to edit.
4. On the **Rules** tab in the right pane, choose **Edit web ACL**.

5. To add rules to the web ACL, perform the following steps:
  - a. In the **Rules** list, choose the rule that you want to add.
  - b. Choose **Add rule to web ACL**.
  - c. Repeat steps a and b until you've added all of the rules that you want.
6. If you want to change the order of the rules in the web ACL, use the arrows in the **Order** column. AWS WAF inspects web requests based on the order in which rules appear in the web ACL.
7. To remove a rule from the web ACL, choose the **x** at the right end of the row for that rule. This doesn't delete the rule from AWS WAF, it just removes the rule from this web ACL.
8. To change the action for a rule or the default action for the web ACL, choose the preferred option.
9. Choose **Save changes**.

## Deleting a Web ACL

To delete a web ACL, you must remove the rules that are included in the web ACL and disassociate all CloudFront distributions from the web ACL. Perform the following procedure.

### To delete a web ACL

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose **Web ACLs**.
3. Choose the web ACL that you want to delete.
4. On the **Rules** tab in the right pane, choose **Edit web ACL**.
5. To remove all rules from the web ACL, choose the **x** at the right end of the row for each rule. This doesn't delete the rules from AWS WAF, it just removes the rules from this web ACL.
6. Choose **Update**.
7. Disassociate the web ACL from all CloudFront distributions. On the **Rules** tab, under **AWS resources using this web ACL**, choose the **x** for each CloudFront distribution.
8. On the **Web ACLs** page, confirm that the web ACL that you want to delete is selected, and choose **Delete**.

# Testing Web ACLs

---

To ensure that you don't accidentally configure AWS WAF to block web requests that you want to allow or allow requests that you want to block, we recommend that you test your web ACL thoroughly before you start using it on your website or web application.

## Topics

- [Counting the Web Requests that Match the Rules in a Web ACL \(p. 64\)](#)
- [Viewing a Sample of the Web Requests that CloudFront has Forwarded to AWS WAF \(p. 65\)](#)

## Counting the Web Requests that Match the Rules in a Web ACL

When you add rules to a web ACL, you specify whether you want AWS WAF to allow, block, or count the web requests that match all of the conditions in that rule. We recommend that you begin with the following configuration:

- Configure all of the rules in a web ACL to count web requests
- Set the default action for the web ACL to allow requests

In this configuration, AWS WAF inspects each web request based on the conditions in the first rule. If the web request matches all of the conditions in that rule, AWS WAF increments a counter for that rule. Then AWS WAF inspects the web request based on the conditions in the next rule and, if the request matches all of the conditions in that rule, AWS WAF increments a counter for that rule. This continues until AWS WAF has inspected the request based on the conditions in all of your rules.

After you've configured all of the rules in a web ACL to count requests and associated the web ACL with a CloudFront distribution, you can view the resulting counts in an Amazon CloudWatch graph. For each rule in a web ACL and for all of the requests that CloudFront forwards to AWS WAF for a web ACL, CloudWatch lets you view data for the preceding hour or preceding three hours, change the interval between data points, and change the calculation that CloudWatch performs on the data, such as maximum, minimum, average, or sum.

### Note

AWS WAF is a global service and metrics are available only when you choose the **US East (N. Virginia)** region in the AWS console. If you choose another region, no AWS WAF metrics will appear in the CloudWatch console.

### To view data for the rules in a web ACL

1. Sign in to the AWS Management Console and open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, under **Metrics**, choose **WAF**.
3. Select the check box for the web ACL that you want to view data for.
4. Change the applicable settings:

**Statistic**

Choose the calculation that CloudWatch performs on the data.

**Time range**

Choose whether you want to view data for the preceding hour or the preceding three hours.


**Period**

Choose the interval between data points in the graph.

**Rules**

Choose the rules for which you want to view data.

Note the following:

- If you just associated a web ACL with a CloudFront distribution, you might need to wait a few minutes for data to appear in the graph and for the metric for the web ACL to appear in the list of available metrics.
  - If you associate more than one web distribution with a web ACL, the CloudWatch data will include all of the requests for all of the distributions that are associated with the web ACL.
  - You can hover the mouse cursor over a data point to get more information.
  - The graph doesn't refresh itself automatically. To update the display, choose the refresh  icon.
5. (Optional) View detailed information about individual requests that CloudFront has forwarded to AWS WAF. For more information, see [Viewing a Sample of the Web Requests that CloudFront has Forwarded to AWS WAF \(p. 65\)](#).
  6. If you determine that a rule is intercepting requests that you don't want it to, change the applicable settings. For more information, see [Creating and Configuring a Web Access Control List \(Web ACL\) \(p. 37\)](#).

When you're satisfied that all of your rules are intercepting only the correct requests, change the action for each of your rules to **Allow** or **Block**. For more information, see [Editing a Web ACL \(p. 62\)](#).

## Viewing a Sample of the Web Requests that CloudFront has Forwarded to AWS WAF

In the AWS WAF console, you can view a sample of the requests that CloudFront has forwarded to AWS WAF for inspection. For each sampled request, you can view detailed data about the request, such as the originating IP address and the headers included in the request. You can also view which rule the request matched, and whether the rule is configured to allow or block requests.

The sample of requests contains up to 100 requests that matched all of the conditions in each rule and another 100 requests for the default action, which applies to requests that didn't match all of the conditions in any rule. The requests in the sample come from all of the CloudFront edge locations that have received requests for your content in the previous 15 minutes.

**To view a sample of the web requests that CloudFront has forwarded to AWS WAF**

1. Sign in to the AWS Management Console and open the AWS WAF console at <https://console.aws.amazon.com/waf/>.
2. In the navigation pane, choose the web ACL for which you want to view requests.
3. In the right pane, choose the **Requests** tab.

The **Sampled requests** table displays the following values for each request:

**Source IP**

Either the IP address that the request originated from or, if the viewer used an HTTP proxy or a load balancer to send the request, the IP address of the proxy or load balancer.

**URI**

The part of a URL that identifies a resource, for example, `/images/daily-ad.jpg`.

**Matches rule**

Identifies the first rule in the web ACL for which the web request matched all of the conditions. If a web request doesn't match all of the conditions in any rule in the web ACL, the value of **Matches rule** is **Default**.

Note that when a web request matches all of the conditions in a rule and the action for that rule is **Count**, AWS WAF continues inspecting the web request based on subsequent rules in the web ACL. In this case, a web request could appear twice in the list of sampled requests: once for the rule that has an action of **Count** and again for a subsequent rule or for the default action.

**Action**

Indicates whether the action for the corresponding rule is **Allow**, **Block**, or **Count**.

**Time**

The time that AWS WAF received the request from CloudFront.

4. To display additional information about the request, choose the arrow on the left side of the IP address for that request. AWS WAF displays the following information:

**Source IP**

The same IP address as the value in the **Source IP** column in the table.

**Country**

The two-letter country code of the country that the request originated from. If the viewer used an HTTP proxy or a load balancer to send the request, this is the two-letter country code of the country that the HTTP proxy or a load balancer is in.

For a list of two-letter country codes and the corresponding country names, see the Wikipedia entry [ISO 3166-1 alpha-2](#).

**Method**

The HTTP request method for the request: **GET**, **HEAD**, **OPTIONS**, **PUT**, **POST**, **PATCH**, or **DELETE**.

**URI**

The same URI as the value in the **URI** column in the table.

**Request headers**

The request headers and header values in the request.

5. To refresh the list of sample requests, choose **Get new samples**.

# Logging AWS WAF API Calls with AWS CloudTrail

---

AWS WAF is integrated with CloudTrail, a service that captures all of the AWS WAF API calls and delivers the log files to an Amazon S3 bucket that you specify. CloudTrail captures API calls from the AWS WAF console or from your code to the AWS WAF APIs. Using the information collected by CloudTrail, you can determine the request that was made to AWS WAF, the source IP address from which the request was made, who made the request, when it was made, and so on.

To learn more about CloudTrail, including how to configure and enable it, see the [AWS CloudTrail User Guide](#).

## AWS WAF Information in CloudTrail

When CloudTrail logging is enabled in your AWS account, API calls made to AWS WAF actions are tracked in CloudTrail log files, where they are written with other AWS service records. CloudTrail determines when to create and write to a new file based on a time period and file size.

All AWS WAF actions are logged by CloudTrail and are documented in the [AWS WAF API Reference](#). For example, calls to **ListWebACL**, **UpdateWebACL** and **DeleteWebACL** generate entries in the CloudTrail log files.

Every log entry contains information about who generated the request. The user identity information in the log entry helps you determine the following:

- Whether the request was made with root or IAM user credentials
- Whether the request was made with temporary security credentials for a role or federated user
- Whether the request was made by another AWS service

For more information, see the [CloudTrail userIdentity Element](#).

You can store your log files in your Amazon S3 bucket for as long as you want, but you can also define Amazon S3 lifecycle rules to archive or delete log files automatically. By default, your log files are encrypted with Amazon S3 server-side encryption (SSE).



If you want to be notified upon log file delivery, you can configure CloudTrail to publish Amazon SNS notifications when new log files are delivered. For more information, see [Configuring Amazon SNS Notifications for CloudTrail](#).

You can also aggregate AWS WAF log files from multiple AWS regions and multiple AWS accounts into a single Amazon S3 bucket.

For more information, see [Receiving CloudTrail Log Files from Multiple Regions](#) and [Receiving CloudTrail Log Files from Multiple Accounts](#).

## Understanding AWS WAF Log File Entries

CloudTrail log files can contain one or more log entries. Each entry lists multiple JSON-formatted events. A log entry represents a single request from any source and includes information about the requested action, the date and time of the action, request parameters, and so on. Log entries are not an ordered stack trace of the public API calls, so they do not appear in any specific order.

The following example shows a CloudTrail log entry that demonstrates the following actions (see the `eventName` elements):

- `CreateRule`
- `GetRule`
- `UpdateRule`
- `DeleteRule`

```
{
  "Records": [
    {
      "eventVersion": "1.03",
      "userIdentity": {
        "type": "IAMUser",
        "principalId": "AIDAIEP4IT4TPDEXAMPLE",
        "arn": "arn:aws:iam::777777777777:user/nate",
        "accountId": "777777777777",
        "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
        "userName": "nate"
      },
      "eventTime": "2016-04-25T21:35:14Z",
      "eventSource": "waf.amazonaws.com",
      "eventName": "CreateRule",
      "awsRegion": "us-west-2",
      "sourceIPAddress": "AWS Internal",
      "userAgent": "console.amazonaws.com",
      "requestParameters": {
        "name": "0923ab32-7229-49f0-a0e3-66c81example",
        "changeToken": "19434322-8685-4ed2-9c5b-9410bexample",
        "metricName": "0923ab32722949f0a0e366c81example"
      },
      "responseElements": {
        "rule": {
          "metricName": "0923ab32722949f0a0e366c81example",
          "ruleId": "12132e64-6750-4725-b714-e7544example",
          "predicates": [
```

**AWS WAF Developer Guide**  
**Understanding AWS WAF Log File Entries**

---

```
    ],
    "name": "0923ab32-7229-49f0-a0e3-66c81example"
  },
  "changeToken": "19434322-8685-4ed2-9c5b-9410bexample"
},
"requestID": "4e6b66f9-d548-11e3-a8a9-73e33example",
"eventID": "923f4321-d378-4619-9b72-4605bexample",
"eventType": "AwsApiCall",
"apiVersion": "2015-08-24",
"recipientAccountId": "777777777777"
},
{
  "eventVersion": "1.03",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "AIDAIEP4IT4TPDEXAMPLE",
    "arn": "arn:aws:iam::777777777777:user/nate",
    "accountId": "777777777777",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "userName": "nate"
  },
  "eventTime": "2016-04-25T21:35:22Z",
  "eventSource": "waf.amazonaws.com",
  "eventName": "GetRule",
  "awsRegion": "us-west-2",
  "sourceIPAddress": "AWS Internal",
  "userAgent": "console.amazonaws.com",
  "requestParameters": {
    "ruleId": "723c2943-82dc-4bc1-a29b-c7d73example"
  },
  "responseElements": null,
  "requestID": "8e4f3211-d548-11e3-a8a9-73e33example",
  "eventID": "an236542-d1f9-4639-bb3d-8d2bbexample",
  "eventType": "AwsApiCall",
  "apiVersion": "2015-08-24",
  "recipientAccountId": "777777777777"
},
{
  "eventVersion": "1.03",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "AIDAIEP4IT4TPDEXAMPLE",
    "arn": "arn:aws:iam::777777777777:user/nate",
    "accountId": "777777777777",
    "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
    "userName": "nate"
  },
  "eventTime": "2016-04-25T21:35:13Z",
  "eventSource": "waf.amazonaws.com",
  "eventName": "UpdateRule",
  "awsRegion": "us-west-2",
  "sourceIPAddress": "AWS Internal",
  "userAgent": "console.amazonaws.com",
  "requestParameters": {
    "ruleId": "7237b123-7903-4d9e-8176-9d71dexample",
    "changeToken": "32343a11-35e2-4dab-81d8-6d408example",
    "updates": [
      {
```

**AWS WAF Developer Guide**  
**Understanding AWS WAF Log File Entries**

---

```
        "predicate": {
            "type": "SizeConstraint",
            "dataId": "9239c032-bbbe-4b80-909b-782c0example",
            "negated": false
        },
        "action": "INSERT"
    }
]
},
"responseElements": {
    "changeToken": "32343a11-35e2-4dab-81d8-6d408example"
},
"requestID": "11918283-0b2d-11e6-9ccc-f9921example",
"eventID": "00032abc-5bce-4237-a8ee-5f1a9example",
"eventType": "AwsApiCall",
"apiVersion": "2015-08-24",
"recipientAccountId": "777777777777"
},
{
    "eventVersion": "1.03",
    "userIdentity": {
        "type": "IAMUser",
        "principalId": "AIDAIEP4IT4TPDEXAMPLE",
        "arn": "arn:aws:iam::777777777777:user/nate",
        "accountId": "777777777777",
        "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
        "userName": "nate"
    },
    "eventTime": "2016-04-25T21:35:28Z",
    "eventSource": "waf.amazonaws.com",
    "eventName": "DeleteRule",
    "awsRegion": "us-west-2",
    "sourceIPAddress": "AWS Internal",
    "userAgent": "console.amazonaws.com",
    "requestParameters": {
        "changeToken": "fd232003-62de-4ea3-853d-52932example",
        "ruleId": "3e3e2d11-fd8b-4333-8b03-1da95example"
    },
    "responseElements": {
        "changeToken": "fd232003-62de-4ea3-853d-52932example"
    },
    "requestID": "b23458a1-0b2d-11e6-9ccc-f9928example",
    "eventID": "a3236565-1a1a-4475-978e-81c12example",
    "eventType": "AwsApiCall",
    "apiVersion": "2015-08-24",
    "recipientAccountId": "777777777777"
}
]
}
```

# How AWS WAF Works with Amazon CloudFront Features

---

AWS WAF integrates easily with Amazon CloudFront. When you create a web ACL, you specify one or more distributions that you want AWS WAF to inspect, and AWS WAF starts to allow, block, or count web requests for those distributions based on the conditions that you identified in the web ACL. This chapter describes a few ways that you can configure CloudFront to make CloudFront and AWS WAF work better together.

## Topics

- [Using AWS WAF with CloudFront Custom Error Pages \(p. 71\)](#)
- [Using AWS WAF with CloudFront Geo Restriction \(p. 72\)](#)
- [Choosing the HTTP Methods that CloudFront Responds to \(p. 72\)](#)

## Using AWS WAF with CloudFront Custom Error Pages

When AWS WAF blocks a web request based on the conditions that you specified, it returns an HTTP 403 (Forbidden) status code to CloudFront, and Amazon CloudFront returns that status code to the viewer. The viewer displays a brief and sparsely formatted default message similar to this:

```
Forbidden: You don't have permission to access /myfilename.html on this server.
```

If you'd rather display a custom error message, possibly using the same formatting as the rest of your website, you can configure CloudFront to return to the viewer an object (for example, an HTML file) that contains your custom error message.

### Note

CloudFront can't distinguish between an HTTP 403 status code that is returned by your origin and one that is returned by AWS WAF when a request is blocked, so you can't return different custom error pages based on the different causes of an HTTP 403 status code.

For more information about CloudFront custom error pages, see [Customizing Error Responses](#) in the *Amazon CloudFront Developer Guide*.

## Using AWS WAF with CloudFront Geo Restriction

You can use the Amazon CloudFront *geo restriction* feature, also known as *geoblocking*, to prevent users in specific geographic locations from accessing content that you're distributing through a CloudFront web distribution. If you want to block web requests from specific countries and also block requests based on other conditions, you can use CloudFront geo restriction in conjunction with AWS WAF. CloudFront returns the same HTTP status code to viewers—HTTP 403 (Forbidden)—whether they try to access your content from a country on a CloudFront geo restriction black list or whether the request is blocked by AWS WAF.

### Note

You can see the two-letter country code of the country that requests originate from in the sample of web requests for a web ACL. For more information, see [Viewing a Sample of the Web Requests that CloudFront has Forwarded to AWS WAF](#) (p. 65).

For more information about CloudFront geo restriction, see [Restricting the Geographic Distribution of Your Content](#) in the *Amazon CloudFront Developer Guide*.

## Choosing the HTTP Methods that CloudFront Responds to

When you create an Amazon CloudFront web distribution, you choose the HTTP methods that you want CloudFront to process and forward to your origin. You can choose from the following options:

- **GET, HEAD** – You can use CloudFront only to get objects from your origin or to get object headers.
- **GET, HEAD, OPTIONS** – You can use CloudFront only to get objects from your origin, get object headers, or retrieve a list of the options that your origin server supports.
- **GET, HEAD, OPTIONS, PUT, POST, PATCH, DELETE** – You can use CloudFront to get, add, update, and delete objects, and to get object headers. In addition, you can perform other POST operations such as submitting data from a web form.

You can also use AWS WAF string match conditions to allow or block requests based on the HTTP method, as described in [Working with String Match Conditions](#) (p. 52). If you want to use a combination of methods that CloudFront supports, such as `GET` and `HEAD`, then you don't need to configure AWS WAF to block requests that use the other methods. If you want to allow a combination of methods that CloudFront doesn't support, such as `GET`, `HEAD`, and `POST`, you can configure CloudFront to respond to all methods, and then use AWS WAF to block requests that use other methods.

For more information about choosing the methods that CloudFront responds to, see [Allowed HTTP Methods](#) in the topic [Values that You Specify When You Create or Update a Web Distribution](#) in the *Amazon CloudFront Developer Guide*.

# Authentication and Access Control for AWS WAF

---

Access to AWS WAF requires credentials. Those credentials must have permissions to access AWS resources, such as an AWS WAF resource or an Amazon S3 bucket. The following sections provide details on how you can use [AWS Identity and Access Management \(IAM\)](#) and AWS WAF to help secure access to your resources.

- [Authentication](#) (p. 73)
- [Access Control](#) (p. 74)

## Authentication

You can access AWS as any of the following types of identities:

- **AWS account root user** – When you sign up for AWS, you provide an email address and password that is associated with your AWS account. These are your *root credentials* and they provide complete access to all of your AWS resources.

### Important

For security reasons, we recommend that you use the root credentials only to create an *administrator user*, which is an *IAM user* with full permissions to your AWS account. Then, you can use this administrator user to create other IAM users and roles with limited permissions. For more information, see [IAM Best Practices](#) and [Creating an Admin User and Group](#) in the *IAM User Guide*.

- **IAM user** – An *IAM user* is simply an identity within your AWS account that has specific custom permissions (for example, permissions to create a rule in AWS WAF). You can use an IAM user name and password to sign in to secure AWS webpages like the [AWS Management Console](#), [AWS Discussion Forums](#), or the [AWS Support Center](#).

In addition to a user name and password, you can also generate [access keys](#) for each user. You can use these keys when you access AWS services programmatically, either through [one of the several SDKs](#) or by using the [AWS Command Line Interface \(CLI\)](#). The SDK and CLI tools use the access keys to cryptographically sign your request. If you don't use the AWS tools, you must sign the request yourself. AWS WAF supports *Signature Version 4*, a protocol for authenticating inbound API requests.

For more information about authenticating requests, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

- **IAM role** – An [IAM role](#) is another IAM identity you can create in your account that has specific permissions. It is similar to an *IAM user*, but it is not associated with a specific person. An IAM role enables you to obtain temporary access keys that can be used to access AWS services and resources. IAM roles with temporary credentials are useful in the following situations:
  - **Federated user access** – Instead of creating an IAM user, you can use preexisting user identities from AWS Directory Service, your enterprise user directory, or a web identity provider. These are known as *federated users*. AWS assigns a role to a federated user when access is requested through an [identity provider](#). For more information about federated users, see [Federated Users and Roles](#) in the *IAM User Guide*.
  - **Cross-account access** – You can use an IAM role in your account to grant another AWS account permissions to access your account's resources. For an example, see [Tutorial: Delegate Access Across AWS Accounts Using IAM Roles](#) in the *IAM User Guide*.
  - **AWS service access** – You can use an IAM role in your account to grant an AWS service permissions to access your account's resources. For example, you can create a role that allows Amazon Redshift to access an Amazon S3 bucket on your behalf and then load data stored in the bucket into an Amazon Redshift cluster. For more information, see [Creating a Role to Delegate Permissions to an AWS Service](#) in the *IAM User Guide*.
  - **Applications running on Amazon EC2** – Instead of storing access keys within the EC2 instance for use by applications running on the instance and making AWS API requests, you can use an IAM role to manage temporary credentials for these applications. To assign an AWS role to an EC2 instance and make it available to all of its applications, you can create an instance profile that is attached to the instance. An instance profile contains the role and enables programs running on the EC2 instance to get temporary credentials. For more information, see [Using Roles for Applications on Amazon EC2](#) in the *IAM User Guide*.

## Access Control

You can have valid credentials to authenticate your requests, but unless you have permissions you cannot create or access AWS WAF resources. For example, you must have permissions to create an AWS WAF *web ACL* or *rule*.

The following sections describe how to manage permissions for AWS WAF. We recommend that you read the overview first.

- [Overview of Managing Access Permissions to Your AWS WAF Resources](#) (p. 75)
- [Using Identity-Based Policies \(IAM Policies\) for AWS WAF](#) (p. 79)
- [AWS WAF API Permissions: Actions, Resources, and Conditions Reference](#) (p. 83)

# Overview of Managing Access Permissions to Your AWS WAF Resources

Every AWS resource is owned by an AWS account, and permissions to create or access a resource are governed by permissions policies. An account administrator can attach permissions policies to IAM identities (that is, users, groups, and roles), and some services also support attaching permissions policies to resources.

## Note

An *account administrator* (or administrator user) is a user with administrator privileges. For more information, see [IAM Best Practices](#) in the *IAM User Guide*.

When granting permissions, you decide who is getting the permissions, the resources they get permissions for, and the specific operations that you want to allow on those resources.

## Topics

- [AWS WAF Resources and Operations](#) (p. 75)
- [Understanding Resource Ownership](#) (p. 76)
- [Managing Access to Resources](#) (p. 76)
- [Specifying Policy Elements: Actions, Effects, Resources, and Principals](#) (p. 78)
- [Specifying Conditions in a Policy](#) (p. 78)

## AWS WAF Resources and Operations

In AWS WAF, the resources are *web ACLs* and *rules*. AWS WAF also supports conditions such as *byte match*, *IP match*, and *size constraint*.

These resources and conditions have unique Amazon Resource Names (ARNs) associated with them as shown in the following table.

Name in WAF console	Name in WAF SDK/CLI	ARN Format	
Web ACL	WebACL	arn:aws:waf:: <i>account</i> : <i>webacl</i> / <i>ID</i>	
Rule	Rule	arn:aws:waf:: <i>account</i> : <i>rule</i> / <i>ID</i>	
String match condition	ByteMatchSet	arn:aws:waf:: <i>account</i> : <i>bytematchset</i> / <i>ID</i>	
SQL injection match condition	SqlInjectionMatchSet	arn:aws:waf:: <i>account</i> : <i>sqlinjectionset</i> / <i>ID</i>	
Size constraint condition	SizeConstraintSet	arn:aws:waf:: <i>account</i> : <i>sizeconstraintset</i> / <i>ID</i>	
IP match condition	IPSet	arn:aws:waf:: <i>account</i> : <i>ipset</i> / <i>ID</i>	
Cross-site scripting match condition	XssMatchSet	arn:aws:waf:: <i>account</i> : <i>xssmatchset</i> / <i>ID</i>	



To allow or deny access to a subset of AWS WAF resources, include the ARN of the resource in the `resource` element of your policy. The ARNs for AWS WAF have the following format:

```
arn:aws:waf::account:resource/ID
```

Replace the *account*, *resource*, and *ID* variables with valid values. Valid values can be the following:

- *account*: The ID of your AWS account. You must specify a value.
- *resource*: The type of AWS WAF resource.
- *ID*: The ID of the AWS WAF resource, or a wildcard (\*) to indicate all resources of the specified type that are associated with the specified AWS account.

For example, the following ARN specifies all web ACLs for the account 111122223333:

```
arn:aws:waf::111122223333:webacl/*
```

For more information, see [Resources](#) in the *IAM User Guide*.

AWS WAF provides a set of operations to work with AWS WAF resources. For a list of available operations, see [Actions](#).

## Understanding Resource Ownership

A *resource owner* is the AWS account that created the resource. That is, the resource owner is the AWS account of the *principal entity* (the root account, an IAM user, or an IAM role) that authenticates the request that creates the resource. The following examples illustrate how this works:

- If you use the root account credentials of your AWS account to create an AWS WAF resource, your AWS account is the owner of the resource.
- If you create an IAM user in your AWS account and grant permissions to create an AWS WAF resource to that user, the user can create an AWS WAF resource. However, your AWS account, to which the user belongs, owns the AWS WAF resource.
- If you create an IAM role in your AWS account with permissions to create a AWS WAF resource, anyone who can assume the role can create a AWS WAF resource. Your AWS account, to which the role belongs, owns the AWS WAF resource.

## Managing Access to Resources

A *permissions policy* describes who has access to what. The following section explains the available options for creating permissions policies.

### Note

This section discusses using IAM in the context of AWS WAF. It doesn't provide detailed information about the IAM service. For complete IAM documentation, see [What Is IAM?](#) in the *IAM User Guide*. For information about IAM policy syntax and descriptions, see [AWS IAM Policy Reference](#) in the *IAM User Guide*.

Policies attached to an IAM identity are referred to as *identity-based* policies (IAM policies) and policies attached to a resource are referred to as *resource-based* policies. AWS WAF only supports identity-based (IAM policies).

## Topics

- [Identity-Based Policies \(IAM Policies\)](#) (p. 77)
- [Resource-Based Policies](#) (p. 78)

## Identity-Based Policies (IAM Policies)

You can attach policies to IAM identities. For example, you can do the following:

- **Attach a permissions policy to a user or a group in your account** – An account administrator can use a permissions policy that is associated with a particular user to grant permissions for that user to create an AWS WAF resource.
- **Attach a permissions policy to a role (grant cross-account permissions)** – You can attach an identity-based permissions policy to an IAM role to grant cross-account permissions. For example, the administrator in Account A can create a role to grant cross-account permissions to another AWS account (for example, Account B) or an AWS service as follows:
  1. Account A administrator creates an IAM role and attaches a permissions policy to the role that grants permissions on resources in Account A.
  2. Account A administrator attaches a trust policy to the role identifying Account B as the principal who can assume the role.
  3. Account B administrator can then delegate permissions to assume the role to any users in Account B. Doing this allows users in Account B to create or access resources in Account A. The principal in the trust policy can also be an AWS service principal if you want to grant an AWS service permissions to assume the role.

For more information about using IAM to delegate permissions, see [Access Management](#) in the *IAM User Guide*.

The following is an example policy that grants permissions for the `waf:ListRules` action on all resources. In the current implementation, AWS WAF doesn't support identifying specific resources using the resource ARNs (also referred to as resource-level permissions) for some of the API actions, so you must specify a wildcard character (\*).

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "ListRules",
      "Effect": "Allow",
      "Action": [
        "waf:ListRules"
      ],
      "Resource": "*"
    }
  ]
}
```

For more information about using identity-based policies with AWS WAF, see [Using Identity-Based Policies \(IAM Policies\) for AWS WAF](#) (p. 79). For more information about users, groups, roles, and permissions, see [Identities \(Users, Groups, and Roles\)](#) in the *IAM User Guide*.

## Resource-Based Policies

Other services, such as Amazon S3, also support resource-based permissions policies. For example, you can attach a policy to an S3 bucket to manage access permissions to that bucket. AWS WAF doesn't support resource-based policies.

## Specifying Policy Elements: Actions, Effects, Resources, and Principals

For each AWS WAF resource (see [AWS WAF Resources and Operations \(p. 75\)](#)), the service defines a set of API operations (see [AWS WAF API Permissions: Actions, Resources, and Conditions Reference \(p. 83\)](#)). To grant permissions for these API operations, AWS WAF defines a set of actions that you can specify in a policy. Note that performing an API operation can require permissions for more than one action. When granting permissions for specific actions, you also identify the resource on which the actions are allowed or denied.

The following are the most basic policy elements:

- **Resource** – In a policy, you use an Amazon Resource Name (ARN) to identify the resource to which the policy applies. For more information, see [AWS WAF Resources and Operations \(p. 75\)](#).
- **Action** – You use action keywords to identify resource operations that you want to allow or deny. For example, the `waf:CreateRule` permission allows the user permissions to perform the AWS WAF `CreateRule` operation.
- **Effect** – You specify the effect when the user requests the specific action—this can be either allow or deny. If you don't explicitly grant access to (allow) a resource, access is implicitly denied. You can also explicitly deny access to a resource, which you might do to make sure that a user cannot access it, even if a different policy grants access.
- **Principal** – In identity-based policies (IAM policies), the user that the policy is attached to is the implicit principal. AWS WAF doesn't support resource-based policies.

To learn more about IAM policy syntax and descriptions, see [AWS IAM Policy Reference](#) in the *IAM User Guide*.

For a table showing all of the AWS WAF API actions and the resources that they apply to, see [AWS WAF API Permissions: Actions, Resources, and Conditions Reference \(p. 83\)](#).

## Specifying Conditions in a Policy

When you grant permissions, you can use the IAM policy language to specify the conditions when a policy should take effect. For example, you might want a policy to be applied only after a specific date. For more information about specifying conditions in a policy language, see [Condition](#) in the *IAM User Guide*.

To express conditions, you use predefined condition keys. There are no condition keys specific to AWS WAF. However, there are AWS-wide condition keys that you can use as appropriate. For a complete list of AWS-wide keys, see [Available Keys for Conditions](#) in the *IAM User Guide*.

## Using Identity-Based Policies (IAM Policies) for AWS WAF

This topic provides examples of identity-based policies that demonstrate how an account administrator can attach permissions policies to IAM identities (that is, users, groups, and roles) and thereby grant permissions to perform operations on AWS WAF resources.

### Important

We recommend that you first review the introductory topics that explain the basic concepts and options available for you to manage access to your AWS WAF resources. For more information, see [Overview of Managing Access Permissions to Your AWS WAF Resources \(p. 75\)](#).

The following shows an example of a permissions policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "CreateFunctionPermissions",
      "Effect": "Allow",
      "Action": [
        "waf:ListWebACLs",
        "waf:ListRules",
        "waf:GetWebACL",
        "waf:GetRule",
        "cloudwatch:ListMetrics",
        "waf:GetSampledRequests"
      ],
      "Resource": "*"
    },
    {
      "Sid": "PermissionToPassAnyRole",
      "Effect": "Allow",
      "Action": [
        "iam:PassRole"
      ],
      "Resource": "arn:aws:iam::account-id:role/*"
    }
  ]
}
```

The policy has two statements:

- The first statement grants permissions to view statistics for AWS WAF web ACLs, using the `waf:ListWebACLs`, `waf:ListRules`, `waf:GetWebACL`, `waf:GetRule`, `cloudwatch:ListMetrics`, and `waf:GetSampledRequests` Actions. AWS WAF doesn't support permissions for some of these actions at the resource-level. Therefore, the policy specifies a wildcard character (\*) as the `Resource` value.
- The second statement grants permissions for the IAM action `iam:PassRole` on IAM roles. The wildcard character (\*) at the end of the `Resource` value means that the statement allows permissions for the `iam:PassRole` action on any IAM role. To limit these permissions to a specific role, replace the wildcard character (\*) in the resource ARN with the specific role name.

The policy doesn't specify the `Principal` element because in an identity-based policy you don't specify the principal who gets the permissions. When you attach a policy to a user, the user is the implicit principal. When you attach a permissions policy to an IAM role, the principal identified in the role's trust policy gets the permissions.

For a table showing all of the AWS WAF API actions and the resources that they apply to, see [AWS WAF API Permissions: Actions, Resources, and Conditions Reference \(p. 83\)](#).

## Topics

- [Permissions Required to Use the AWS WAF Console \(p. 80\)](#)
- [AWS Managed \(Predefined\) Policies for AWS WAF \(p. 80\)](#)
- [Customer Managed Policy Examples \(p. 80\)](#)

## Permissions Required to Use the AWS WAF Console

The AWS WAF console provides an integrated environment for you to create and manage AWS WAF resources. The console provides many features and workflows that often require permissions to create a AWS WAF resource in addition to the API-specific permissions documented in the [AWS WAF API Permissions: Actions, Resources, and Conditions Reference \(p. 83\)](#). For more information about these additional console permissions, see [Customer Managed Policy Examples \(p. 80\)](#).

## AWS Managed (Predefined) Policies for AWS WAF

AWS addresses many common use cases by providing standalone IAM policies that are created and administered by AWS. Managed policies grant necessary permissions for common use cases so you can avoid having to investigate what permissions are needed. For more information, see [AWS Managed Policies](#) in the *IAM User Guide*.

The following AWS managed policies, which you can attach to users in your account, are specific to AWS WAF and are grouped by use case scenario:

- **AWSWAFFullAccess** – Grants full access to AWS WAF resources.
- **AWSWAFReadOnlyAccess** – Grants read-only access to AWS WAF resources.

### Note

You can review these permissions policies by signing in to the IAM console and searching for specific policies there.

You can also create your own custom IAM policies to allow permissions for AWS WAF API operations and resources. You can attach these custom policies to the IAM users or groups that require those permissions or to custom execution roles (IAM roles) that you create for your AWS WAF resources.

## Customer Managed Policy Examples

The examples in this section provide a group of sample policies that you can attach to a user. If you are new to creating policies, we recommend that you first create an IAM user in your account and attach the policies to the user in sequence, as outlined in the steps in this section.

You can use the console to verify the effects of each policy as you attach the policy to the user. Initially, the user doesn't have permissions, and the user won't be able to do anything in the console. As you attach policies to the user, you can verify that the user can perform various operations in the console.

We recommend that you use two browser windows: one to create the user and grant permissions, and the other to sign in to the AWS Management Console using the user's credentials and verify permissions as you grant them to the user.

For examples that show how to create an IAM role that you can use as an execution role for your AWS WAF resource, see [Creating IAM Roles](#) in the *IAM User Guide*.

## Example Topics

- [Example 1: Give Users Read-only Access to AWS WAF, CloudFront, and CloudWatch](#) (p. 81)
- [Example 2: Give Users Full Access to AWS WAF, CloudFront, and CloudWatch](#) (p. 82)
- [Example 3: Granting Access to a Specified AWS Account](#) (p. 82)
- [Example 4: Granting Access to a Specified Web ACL](#) (p. 83)

## Create an IAM User

First, you need to create an IAM user, add the user to an IAM group with administrative permissions, and then grant administrative permissions to the IAM user that you created. You can then access AWS using a special URL and the user's credentials.

For instructions, see [Creating Your First IAM User and Administrators Group](#) in the *IAM User Guide*.

## Example 1: Give Users Read-only Access to AWS WAF, CloudFront, and CloudWatch

The following policy grants users read-only access to AWS WAF resources, to Amazon CloudFront web distributions, and to Amazon CloudWatch metrics. It's useful for users who need permission to view the settings in AWS WAF conditions, rules, and web ACLs to see which distribution is associated with a web ACL, and to monitor metrics and a sample of requests in CloudWatch. These users can't create, update, or delete AWS WAF resources.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Action": [
        "waf:Get*",
        "waf:List*",
        "cloudfront:GetDistribution",
        "cloudfront:GetDistributionConfig",
        "cloudfront:ListDistributions",
        "cloudfront:ListDistributionsByWebACLId",
        "cloudwatch:ListMetrics",
        "cloudwatch:GetMetricStatistics"
      ],
      "Effect": "Allow",
      "Resource": "*"
    }
  ]
}
```

## Example 2: Give Users Full Access to AWS WAF, CloudFront, and CloudWatch

The following policy lets users perform any AWS WAF operation, perform any operation on CloudFront web distributions, and monitor metrics and a sample of requests in CloudWatch. It's useful for users who are AWS WAF administrators.

We strongly recommend that you configure multi-factor authentication (MFA) for users who have administrative permissions. For more information, see [Using Multi-Factor Authentication \(MFA\) Devices with AWS](#) in the *IAM User Guide*.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Action": [
        "waf:*",
        "cloudfront:CreateDistribution",
        "cloudfront:GetDistribution",
        "cloudfront:GetDistributionConfig",
        "cloudfront:UpdateDistribution",
        "cloudfront:ListDistributions",
        "cloudfront:ListDistributionsByWebACLId",
        "cloudfront>DeleteDistribution",
        "cloudwatch:ListMetrics",
        "cloudwatch:GetMetricStatistics"
      ],
      "Effect": "Allow",
      "Resource": "*"
    }
  ]
}
```

## Example 3: Granting Access to a Specified AWS Account

This policy grants the following permissions to the account 444455556666:

- Full access to all AWS WAF operations and resources.
- Read and update access to all CloudFront distributions, which allows you to associate web ACLs and CloudFront distributions.
- Read access to all CloudWatch metrics and metric statistics, so you can view CloudWatch data and a sample of requests in the AWS WAF console.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "waf:*"
      ],
      "Resource": [
        "arn:aws:waf::444455556666:*"
      ]
    }
  ]
}
```

```
    },
    {
      "Effect": "Allow",
      "Action": [
        "cloudfront:GetDistribution",
        "cloudfront:GetDistributionConfig",
        "cloudfront:ListDistributions",
        "cloudfront:ListDistributionsByWebACLId",
        "cloudfront:UpdateDistributions",
        "cloudwatch:ListMetrics",
        "cloudwatch:GetMetricStatistics"
      ],
      "Resource": [
        "*"
      ]
    }
  ]
}
```

## Example 4: Granting Access to a Specified Web ACL

This policy grants the following permissions to the `webacl` ID `112233d7c-86b2-458b-af83-51c51example` in the account `444455556666`:

- Full access to AWS WAF Get, Update, and Delete operations and resources

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "waf:*"
      ],
      "Resource": [
        "arn:aws:waf::444455556666:webacl/112233d7c-86b2-458b-af83-51c51example"
      ]
    }
  ]
}
```

## AWS WAF API Permissions: Actions, Resources, and Conditions Reference

When you are setting up [Access Control \(p. 74\)](#) and writing permissions policies that you can attach to an IAM identity (identity-based policies), you can use the following table as a reference. The table lists each AWS WAF API operation, the corresponding actions for which you can grant permissions to perform the action, and the AWS resource for which you can grant the permissions. You specify the actions in the policy's `Action` field, and you specify the resource value in the policy's `Resource` field.



You can use AWS-wide condition keys in your AWS WAF policies to express conditions. For a complete list of AWS-wide keys, see [Available Keys for Conditions](#) in the *IAM User Guide*.

**Note**

To specify an action, use the `waf:` prefix followed by the API operation name (for example, `waf:CreateIPSet`).

**AWS WAF API and Required Permissions for Actions**

[CreateByteMatchSet](#)

**Action(s):** `waf:CreateByteMatchSet`

**Resource:** `arn:aws:waf:account-id:bytematchset/entity-ID`

[CreateIPSet](#)

**Action(s):** `waf:CreateIPSet`

**Resource:** `arn:aws:waf:account-id:ipset/entity-ID`

[CreateRule](#)

**Action(s):** `waf:CreateRule`

**Resource:** `arn:aws:waf:account-id:rule/entity-ID`

[CreateSizeConstraintSet](#)

**Action(s):** `waf:CreateSizeConstraintSet`

**Resource:** `arn:aws:waf:account-id:sizeconstraintset/entity-ID`

[CreateSqlInjectionMatchSet](#)

**Action(s):** `waf:CreateSqlInjectionMatchSet`,

**Resource:** `arn:aws:waf:account-id:sqlinjectionmatchset/entity-ID`

[CreateWebACL](#)

**Action(s):** `waf:CreateWebACL`

**Resource:** `arn:aws:waf:account-id:webacl/entity-ID`

[CreateXssMatchSet](#)

**Action(s):** `waf:CreateXssMatchSet`

**Resource:** `arn:aws:waf:account-id:xssmatchset/entity-ID`

[DeleteByteMatchSet](#)

**Action(s):** `waf>DeleteByteMatchSet`,

**Resource:** `arn:aws:waf:account-id:bytematchset/entity-ID`

[DeleteIPSet](#)

**Action(s):** `waf>DeleteIPSet`

**Resource:** `arn:aws:waf:account-id:ipset/entity-ID`

[DeleteRule](#)

**Action(s):** `waf>DeleteRule`

**Resource:** `arn:aws:waf:account-id:rule/entity-ID`

[DeleteSizeConstraintSet](#)

**Action(s):** `waf>DeleteSizeConstraintSet`

**Resource:** `arn:aws:waf:account-id:sizeconstraintset/entity-ID`

[DeleteSqlInjectionMatchSet](#)

**Action(s):** `waf>DeleteSqlInjectionMatchSet`

**Resource:** `arn:aws:waf:account-id:sqlinjectionmatchset/entity-ID`

#### DeleteWebACL

**Action(s):** waf:DeleteWebACL

**Resource:** arn:aws:waf:*account-id*:webacl/*entity-ID*

#### DeleteXssMatchSet

**Action(s):** waf:DeleteXssMatchSet

**Resource:** arn:aws:waf:*account-id*:xssmatchset/*entity-ID*

#### GetByteMatchSet

**Action(s):** waf:GetByteMatchSet

**Resource:** arn:aws:waf:*account-id*:bytematchset/*entity-ID*

#### GetChangeToken

**Action(s):** waf:GetChangeToken

**Resource:** arn:aws:waf:*account-id*:changetoken/*entity-ID*

#### GetChangeTokenStatus

**Action(s):** waf:GetChangeTokenStatus

**Resource:** arn:aws:waf:*account-id*:changetoken/*token-ID*

#### GetIPSet

**Action(s):** waf:GetIPSet

**Resource:** arn:aws:waf:*account-id*:ipset/*entity-ID*

#### GetRule

**Action(s):** waf:GetRule

**Resource:** arn:aws:waf:*account-id*:rule/*entity-ID*

#### GetSampledRequests

**Action(s):** waf:GetSampledRequests

**Resource:** Resource depends on the parameters that are specified in the API call. You must have access to the rule or webacl that correspond to the request for samples. For example:  
arn:aws:waf:*account-id*:rule/example1 or arn:aws:waf:*account-id*:webacl/example2

#### GetSizeConstraintSet

**Action(s):** waf:GetSizeConstraintSet

**Resource:** arn:aws:waf:*account-id*:sizeconstraintset/*entity-ID*

#### GetSqlInjectionMatchSet

**Action(s):** waf:GetSqlInjectionMatchSet

**Resource:** arn:aws:waf:*account-id*:sqlinjectionmatchset/*entity-ID*

#### GetWebACL

**Action(s):** waf:GetWebACL

**Resource:** arn:aws:waf:*account-id*:webacl/*entity-ID*

#### GetXssMatchSet

**Action(s):** waf:GetXssMatchSet

**Resource:** arn:aws:waf:*account-id*:xssmatchset/*entity-ID*

#### ListByteMatchSets

**Action(s):** waf:ListByteMatchSets

**Resource:** arn:aws:waf:*account-id*:bytematchset/*entity-ID*

#### ListIPSets

**Action(s):** waf:ListIPSets

**Resource:** arn:aws:waf:*account-id*:*ipset/entity-ID*

#### ListRules

**Action(s):** waf:ListRules

**Resource:** arn:aws:waf:*account-id*:*rule/entity-ID*

#### ListSizeConstraintSets

**Action(s):** waf:ListSizeConstraintSets

**Resource:** arn:aws:waf:*account-id*:*sizeconstraintset/entity-ID*

#### ListSqlInjectionMatchSets

**Action(s):** waf:ListSqlInjectionMatchSets

**Resource:** arn:aws:waf:*account-id*:*sqlinjectionmatchset/entity-ID*

#### ListWebACLs

**Action(s):** waf:ListWebACLs

**Resource:** arn:aws:waf:*account-id*:*webacl/entity-ID*

#### ListXssMatchSets

**Action(s):** waf:ListXssMatchSets

**Resource:** arn:aws:waf:*account-id*:*xssmatchset/entity-ID*

#### UpdateByteMatchSet

**Action(s):** waf:UpdateByteMatchSet

**Resource:** arn:aws:waf:*account-id*:*bytematchset/entity-ID*

#### UpdateIPSet

**Action(s):** waf:UpdateIPSet

**Resource:** arn:aws:waf:*account-id*:*ipset/entity-ID*

#### UpdateRule

**Action(s):** waf:UpdateRule

**Resource:** arn:aws:waf:*account-id*:*rule/entity-ID*

#### UpdateSizeConstraintSet

**Action(s):** waf:UpdateSizeConstraintSet

**Resource:** arn:aws:waf:*account-id*:*sizeconstraintset/entity-ID*

#### UpdateSqlInjectionMatchSet

**Action(s):** waf:UpdateSqlInjectionMatchSet

**Resource:** arn:aws:waf:*account-id*:*sqlinjectionmatchset/entity-ID*

#### UpdateWebACL

**Action(s):** waf:UpdateWebACL

**Resource:** arn:aws:waf:*account-id*:*webacl/entity-ID*

#### UpdateXssMatchSet

**Action(s):** waf:UpdateXssMatchSet

**Resource:** arn:aws:waf:*account-id*:*xssmatchset/entity-ID*

# Using the AWS WAF API

---

This section describes how to make requests to the AWS WAF API for creating and managing match sets, rules, and web ACLs. This chapter will acquaint you with the components of requests, the content of responses, and how to authenticate requests.

## Topics

- [Using the AWS SDKs \(p. 87\)](#)
- [Making HTTPS Requests to AWS WAF \(p. 87\)](#)
- [HTTP Responses \(p. 89\)](#)
- [Authenticating Requests \(p. 90\)](#)

## Using the AWS SDKs

If you're using a language that AWS provides an SDK for, use the SDK rather than trying to work your way through the APIs. The SDKs make authentication simpler, integrate easily with your development environment, and provide easy access to AWS WAF commands. For more information about the AWS SDKs, see [Step 3: Download Tools \(p. 7\)](#) in the topic [Setting Up for AWS WAF \(p. 5\)](#).

## Making HTTPS Requests to AWS WAF

AWS WAF requests are HTTPS requests, as defined by [RFC 2616](#). Like any HTTP request, a request to AWS WAF contains a request method, a URI, request headers, and a request body. The response contains an HTTP status code, response headers, and sometimes a response body.

### Request URI

The request URI is always a single forward slash, /.

### HTTP Headers

AWS WAF requires the following information in the header of an HTTP request:

### Host (Required)

The AWS WAF endpoint that specifies where your resources are created. The value of the `Host` header is always `waf.amazonaws.com:443`.

### x-amz-date or Date (Required)

The date used to create the signature contained in the `Authorization` header. Specify the date in ISO 8601 standard format, in UTC time, as in the following example:

```
x-amz-date: 20151007T174952Z
```

You must include either `x-amz-date` or `Date`. (Some HTTP client libraries don't let you set the `Date` header). When an `x-amz-date` header is present, AWS WAF ignores any `Date` header when authenticating the request.

The time stamp must be within 15 minutes of the AWS system time when the request is received. If it isn't, the request fails with the `RequestExpired` error code to prevent someone else from replaying your requests.

### Authorization (Required)

The information required for request authentication. For more information about constructing this header, see [Authenticating Requests \(p. 90\)](#).

### X-Amz-Target (Required)

A concatenation of `AWSWAF_`, the API version without punctuation (`20150824`), a period (`.`), and the name of the operation, for example:

```
AWSWAF_20150824.CreateWebACL
```

### Content-Type (Conditional)

Specifies that the content type is JSON as well as the version of JSON, as in the following example:

```
Content-Type: application/x-amz-json-1.1
```

Condition: Required for POST requests.

### Content-Length (Conditional)

Length of the message (without the headers) according to RFC 2616.

Condition: Required if the request body itself contains information (most toolkits add this header automatically).

The following is an example header for an HTTP request to create a web ACL.

```
POST / HTTP/1.1
Host: waf.amazonaws.com:443
X-Amz-Date: 20151007T174952Z
Authorization: AWS4-HMAC-SHA256
                Credential=AccessKeyID/20151007/us-east-1/waf/aws4_request,
                SignedHeaders=host;x-amz-date;x-amz-target,
                Signature=145b1567ab3c50d929412f28f52c45dbf1e63ec5c66023d232a539a4afd11fd9
X-Amz-Target: AWSWAF_20150824.CreateWebACL
Accept: */*
Content-Type: application/x-amz-json-1.1; charset=UTF-8
Content-Length: 231
Connection: Keep-Alive
```

## HTTP Request Body

Many AWS WAF API actions require you to include JSON-formatted data in the body of the request.

The following example request uses a simple JSON statement to update an `IPSet` (known in the console as an IP match condition) to include the IP address 192.0.2.44 (represented in CIDR notation as 192.0.2.44/32):

```
POST / HTTP/1.1
Host: waf.amazonaws.com:443
X-Amz-Date: 20151007T174952Z
Authorization: AWS4-HMAC-SHA256
                Credential=AccessKeyID/20151007/us-east-1/waf/aws4_request,
                SignedHeaders=host;x-amz-date;x-amz-target,
                Signature=145b1567ab3c50d929412f28f52c45dbf1e63ec5c66023d232a539a4afd11fd9
X-Amz-Target: AWSWAF_20150824.UpdateIPSet
Accept: */*
Content-Type: application/x-amz-json-1.1; charset=UTF-8
Content-Length: 283
Connection: Keep-Alive

{
  "ChangeToken": "d4c4f53b-9c7e-47ce-9140-0ee5ffffffff",
  "IPSetId": "69d4d072-170c-463d-ab82-0643ffffffff",
  "Updates": [
    {
      "Action": "INSERT",
      "IPSetDescriptor": {
        "Type": "IPV4",
        "Value": "192.0.2.44/32"
      }
    }
  ]
}
```

## HTTP Responses

All AWS WAF API actions include JSON-formatted data in the response.

Here are some important headers in the HTTP response and how you should handle them in your application, if applicable:

### HTTP/1.1

This header is followed by a status code. Status code 200 indicates a successful operation.

Type: String

### x-amzn-RequestId

A value created by AWS WAF that uniquely identifies your request, for example, K2QH8DNOU907N97FNA2GDLL8OBVV4KQNSO5AEMVJF66Q9ASUAAJG. If you have a problem with AWS WAF, AWS can use this value to troubleshoot the problem.

Type: String

### Content-Length

The length of the response body in bytes.

Type: String

**Date**

The date and time that AWS WAF responded, for example, Wed, 07 Oct 2015 12:00:00 GMT.

Type: String

## Error Responses

If a request results in an error, the HTTP response contains the following values:

- A JSON error document as the response body
- Content-Type header: text/xml
- The applicable 3xx, 4xx, or 5xx HTTP status code

Following is an example of a JSON error document:

```
HTTP/1.1 400 Bad Request
x-amzn-RequestId: b0e91dc8-3807-11e2-83c6-5912bf8ad066
x-amzn-ErrorType: ValidationException
Content-Type: application/json
Content-Length: 125
Date: Mon, 26 Nov 2012 20:27:25 GMT

{"message": "1 validation error detected: Value null at 'TargetString' failed to satisfy constraint: Member must not be null"}
```

## Authenticating Requests

If you're using a language for which AWS provides an SDK, we recommend that you use the SDK. All of the AWS SDKs greatly simplify the process of signing requests and save you a significant amount of time when compared with using the AWS WAF API. In addition, the SDKs integrate easily with your development environment and provide easy access to related commands.

AWS WAF requires that you authenticate every request that you send by signing the request. To sign a request, you calculate a digital signature using a cryptographic hash function, which returns a hash value based on the input. The input includes the text of your request and your secret access key. The hash function returns a hash value that you include in the request as your signature. The signature is part of the `Authorization` header of your request.

After receiving your request, AWS WAF recalculates the signature using the same hash function and input that you used to sign the request. If the resulting signature matches the signature in the request, AWS WAF processes the request. If not, the request is rejected.

AWS WAF supports authentication using [AWS Signature Version 4](#). The process for calculating a signature can be broken into three tasks:

**Task 1: Create a Canonical Request**

Create your HTTP request in canonical format as described in [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

**Task 2: Create a String to Sign**

Create a string that you will use as one of the input values to your cryptographic hash function. The string, called the string to sign, is a concatenation of the following values:

- Name of the hash algorithm
- Request date
- Credential scope string
- Canonicalized request from the previous task

The credential scope string itself is a concatenation of date, region, and service information.

For the `X-Amz-Credential` parameter, specify the following:

- The code for the endpoint to which you're sending the request, `us-east-1`
- `waf` for the service abbreviation

For example:

```
X-Amz-Credential=AKIAIOSFODNN7EXAMPLE/20130501/us-east-1/waf/aws4_request
```

### **Task 3: Create a Signature**

Create a signature for your request by using a cryptographic hash function that accepts two input strings:

- Your string to sign, from Task 2.
- A derived key. The derived key is calculated by starting with your secret access key and using the credential scope string to create a series of hash-based message authentication codes (HMACs).



# Limits

AWS WAF has default limits on the number of entities per account. You can [request an increase](#) in these limits.

Resource	Default Limit
Web ACLs per AWS account	10
Rules per AWS account	50
Conditions per AWS account	50

The following limits on AWS WAF entities can't be changed.

Resource	Limit
Rules per web ACL	10
Conditions per rule	10
Filters per cross-site scripting match condition	10
Filters per size constraint condition	10
Filters per SQL injection match condition	10
Filters per string match condition	10
In string match conditions, the number of characters in HTTP header names, when you've configured AWS WAF to inspect the headers in web requests for a specified value	40
In string match conditions, the number of bytes in the value that you want AWS WAF to search for	50
IP address ranges (in CIDR notation) per IP match condition	1000

# Resources

---

The following related resources can help you as you work with this service.

## AWS Resources

Several helpful guides, forums, and other resources are available from Amazon Web Services.

- [AWS WAF Release Notes](#) – A high-level overview of the current release noting any new features, corrections, and known issues.
- [Discussion Forums](#) – A community-based forum for developers to discuss technical questions related to AWS WAF.
- [AWS Support Center](#) – This site brings together information about your recent support cases, and provides links to discussion forums, technical FAQs, the service health dashboard, and information about AWS support plans.
- [AWS Premium Support Information](#) – The primary web page for information about AWS Premium Support, a one-on-one, fast-response support channel to help you build and run applications on AWS Infrastructure Services.
- [Contact Us](#) – Links for inquiring about your billing or account. For technical questions, use the discussion forums or support links above.
- [AWS WAF product information](#) – The primary web page for information about AWS WAF, including features, pricing, and more.
  
- [AWS Training and Courses](#) – Links to role-based and specialty courses as well as self-paced labs to help sharpen your AWS skills and gain practical experience.
- [AWS Developer Tools](#) – Links to developer tools and resources that provide documentation, code samples, release notes, and other information to help you build innovative applications with AWS.
- [AWS Support Center](#) – The hub for creating and managing your AWS Support cases. Also includes links to other helpful resources, such as forums, technical FAQs, service health status, and AWS Trusted Advisor.
- [AWS Support](#) – The primary web page for information about AWS Support, a one-on-one, fast-response support channel to help you build and run applications in the cloud.
- [Contact Us](#) – A central contact point for inquiries concerning AWS billing, account, events, abuse, and other issues.
- [AWS Site Terms](#) – Detailed information about our copyright and trademark; your account, license, and site access; and other topics.

# Document History

- **API Version:** 2015-08-24
- **Latest documentation update:** July 25, 2016

The following table describes important changes in each release of the *AWS WAF Developer Guide*.

Change	API Version	Description	Release Date
Update	2015-08-24	Added information about <a href="#">PCI DSS Compliance (p. 3)</a> for AWS WAF.	July 25, 2016
New Features	2015-08-24	<p>You can now log all your API calls to AWS WAF through AWS CloudTrail, the AWS service that records API calls for your account and delivers log files to your S3 bucket. CloudTrail logs can be used to enable security analysis, track changes to your AWS resources, and aid in compliance auditing. Integrating AWS WAF and CloudTrail lets you determine which requests were made to the AWS WAF API, the source IP address from which each request was made, who made the request, when it was made, and more.</p> <p>If you are already using AWS CloudTrail, you will start seeing AWS WAF API calls in your AWS CloudTrail log. If you haven't turned on AWS CloudTrail for your account, you can turn on CloudTrail from the <a href="#">AWS Management Console</a>. There is no additional charge for turning on CloudTrail, but standard rates for Amazon S3 and Amazon SNS usage apply. Please visit the <a href="#">AWS WAF detail page</a> or the <a href="#">AWS WAF Developer Guide</a> to learn more.</p>	April 28, 2016
New Features	2015-08-24	You can now use AWS WAF to allow, block, or count web requests that appear to contain malicious scripts, known as cross-site scripting or XSS. Attackers sometimes insert malicious scripts into web requests in an effort to exploit vulnerabilities in web applications. For more information, see <a href="#">Working with Cross-site Scripting Match Conditions (p. 38)</a> .	March 29, 2016

Change	API Version	Description	Release Date
New Features	2015-08-24	<p>With this release, AWS WAF adds the following features:</p> <ul style="list-style-type: none"> <li>You can configure AWS WAF to allow, block, or count web requests based on the lengths of specified parts of the requests, such as query strings or URIs. For more information, see <a href="#">Working with Size Constraint Conditions (p. 44)</a>.</li> <li>You can configure AWS WAF to allow, block, or count web requests based on the content in the request body. This is the part of a request that contains any additional data that you want to send to your web server as the HTTP request body, such as data from a form. This feature applies to string match conditions, SQL injection match conditions, and the new size constraint conditions mentioned in the first bullet. For more information, see the following documentation: <ul style="list-style-type: none"> <li><a href="#">Values that You Specify When You Create or Edit String Match Conditions (p. 53)</a></li> <li><a href="#">Values that You Specify When You Create or Edit SQL Injection Match Conditions (p. 49)</a></li> <li><a href="#">Values that You Specify When You Create or Edit Size Constraint Conditions (p. 45)</a></li> </ul> </li> </ul>	January 27, 2016
New Feature	2015-08-24	You can now use the AWS WAF console to choose the CloudFront distributions that you want to associate a web ACL with. For more information, see <a href="#">Associating or Disassociating a Web ACL and a CloudFront Distribution</a> .	November 16, 2015
Initial Release	2015-08-24	This is the first release of the <i>AWS WAF Developer Guide</i> .	October 6, 2015

# AWS Glossary

---

For the latest AWS terminology, see the [AWS Glossary](#) in the *AWS General Reference*.